

# ACROLUX

## Matte Exterior Paint with an Acrylic Base

Acrolux is an acrylic-based, matte decorative exterior paint.



*High resistance to color fading.*

*Resistant to exterior conditions such as rain, snow, humidity, and extreme heat or cold.*

*Provides excellent coverage.*

*Thanks to its water vapor permeability, it allows vapor to escape and the surface to breathe.*

*Water-based, environmentally friendly, and safe for human health.*

	CONTENT: Acrylic-based - water-based		PACKAGING: 13.5 L; 15 L
	THINNING: With a maximum of 15-20% clean water by volume.		DRYING TIME: Drying Time Touch dry (at 23°C): 4-6 hours <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
	PRIMER: San Deco Uniprimer		Fully Dry: 24-48 hours
	APPLICATION TOOL: Roller, brush, spray		COLORING: Vision, RAL, NCS
	NUMBER of COATS: 2		VOC: <i>EU limit value (Directive 2004/42/EC)</i> Category A/C: Exterior walls of mineral substrates (water-based): 40 g/l (2010) ACROLUX: Contains a maximum of 32.6 g/l VOC
	STORAGE and SHELF LIFE: <i>Can be stored for 2 years between +5°C and +35°C in its unopened packaging, in a cool and dry place, protected from direct sunlight.</i>		

**CONSUMPTION** - Single Coat : Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.



With 1 L: 12.5-15.5 m<sup>2</sup> coverage

With 1 kg: 7.5-9 m<sup>2</sup> coverage

Paint consumption per m<sup>2</sup>: 65-80 ml or 110-135 g.

## APPLICATION AREA

Can be used with a suitable primer on exterior surfaces such as plaster, fiber cement, exposed concrete, and cement boards of all types of buildings.

## SURFACE PREPARATION

All dirt, oil, blistered paints, and dust must be cleaned from the surfaces before application.

Surface defects should be repaired with San Deco Acrylic Putty Thick and then primed with San Deco Uniprimer.

It is recommended to use a primer in the same color as the chosen façade color.

## SURFACE CONDITIONS

During application and until the products are completely dry, the ambient and surface temperature should be at least +5°C and at most +35°C.

Do not apply under direct sunlight.

The surfaces to be painted must be completely dry.

Ambient humidity should be below 75% during application.

Surface moisture content should be below 10%.

## APPLICATION

Acrolux should be thinned with a maximum of 15-20% clean water by volume and mixed homogeneously before application.

Apply two (2) coats to the surface using a roller, brush, or spray method.

Allow a minimum of 4 hours between coats.

If multiple batch numbers are used in the same project, mix them in equal proportions before application to avoid batch-based differences.

## HAZARD & PRECAUTIONARY STATEMENTS AND EXPLANATIONS

H317: May cause an allergic skin reaction.

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment required (see label).

P272: Contaminated work clothing should not be allowed out of the workplace.



Complies with TS 7847.



Complies with G Directive.

Note: For more information, refer to the product's Safety Data Sheet (SDS).

This technical data sheet is based on laboratory data under normal conditions. For details not covered above, consult technical staff. The manufacturer cannot be held responsible for errors arising from insufficient information. The right to modify this information is reserved. For detailed information regarding health, safety, transport risks, and precautions, refer to the Material Safety Data Sheet.

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified for ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.