

TERAMIX

Granular Textured Exterior Coating

TERAMIX is a decorative exterior coating with a textured grain finish. Produced in different grain sizes: 1 mm, 1.5 mm, 2 mm, and 3 mm.



The thick film layer formed during application covers surface imperfections.

High resistance to UV rays, alkali, and color fading.

Resistant to exterior weather conditions; unaffected by rain, snow, humidity, extreme heat, or cold.

Due to its water vapor permeability, it allows vapor to escape and enables the surface to breathe.

Water-based, environmentally friendly, and safe for human health.


 **CONTENT:** *Acrylic-based - water-based*

 **PACKAGING:** 25 KG

 **THINNING:** *Ready to use, do not thin.*

 **DRYING TIME:** *Drying Time Touch dry (at 23°C): 4-6 hours*
**drying time may be longer at higher relative humidity and lower temperature.*


 **PRIMER:** *San Deco Uniprimer*


 **Fully Dry:** 24-48 hours

 **APPLICATION TOOL:** *Trowel*

 **COLORING:** -

 **NUMBER of COATS:** 1

 **STORAGE and SHELF LIFE:**
Can be stored for 2 years in its unopened original package, in a cool and dry place, protected from direct sunlight, between +5°C and +35°C.

 **VOC:**
EU Directive 2004/42/EC
Category A/I: Decorative effect coatings (water-based): 200 g/L (2010)
TERAMIX contains a maximum of 40.9 g/L VOC.

CONSUMPTION - Single Coat : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.*



Teramix 1 mm:
With 1 L, 1.0-1.7 m² can be covered.
With 1 kg, 0.55-1.0 m² can be covered.
For 1 m²: 560-1000 ml or 1000-1800 g required.

Teramix 2 mm:
With 1 L, 0.6-0.9 m² can be covered.
With 1 kg, 0.45-0.6 m² can be covered.
For 1 m²: 1200-1800 ml or 2200-3200 g required.

Teramix 1.5 mm:
With 1 L, 0.83-1.06 m² can be covered.
With 1 kg, 0.45-0.6 m² can be covered.
For 1 m²: 940-1200 ml or 1700-2200 g required.

Teramix 3 mm:
With 1 L, 0.6-0.9 m² can be covered.
With 1 kg, 0.25-0.3 m² can be covered.
For 1 m²: 2000-2500 ml or 3500-4500 g required.

APPLICATION AREA

Used on all types of exterior wall surfaces such as traditional plaster, fair-faced concrete, cement boards, and thermal insulation systems, together with the appropriate primer.

SURFACE PREPARATION

All types of dirt, oil, loose paint, and dust must be removed from the surface before application.

Surface defects should be repaired using San Deco Acrylic Putty Thick, and then primed with San Deco Uniprimer.

It is recommended to use a primer tinted in the same color as the selected topcoat.

SURFACE CONDITIONS

During application and until complete drying, ensure that the ambient and surface temperature is between +5°C and +35°C.

Do not apply under direct sunlight.

Surfaces to be coated must be completely dry.

Ambient humidity should be below 75%.

Surface moisture content should be below 10%.

APPLICATION

Before application, Teramix should be mixed thoroughly until homogeneous without thinning.

Apply one uniform coat using a trowel. The application thickness should correspond to the largest aggregate size within the product.

A plastic trowel can be used to create a circular pattern on the surface.

When using multiple batch numbers within the same project, it is recommended to mix batches evenly prior to application to avoid batch-to-batch variations.

HAZARD & PRECAUTIONARY STATEMENTS

H317: May cause an allergic skin reaction.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.

P362 + P364: Take off contaminated clothing and wash before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment (see label).

P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).

This technical data sheet has been prepared based on laboratory data obtained under normal conditions. For further details not included above, please consult technical staff. The manufacturer assumes no responsibility for errors arising from insufficient information. The right to amend this document is reserved by the company. For detailed information regarding health, safety, and transport precautions, please refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified under ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.