

ACRYLIC PUTTY INTERIOR

Acrylic-Based Fine Interior Wall Putty

Acrylic Putty Interior is a fine surface smoothing putty used for surface preparation before applying water-based paints on interior walls.














Has high adhesion (bonding strength) and breathability.


Easy to apply, spreads smoothly on the surface, and reduces paint consumption.

Produces minimal dust during sanding.

It is water-based, friendly to human health and the environment.

 CONTENT: <i>Acrylic-based - water-based</i>	 PACKAGING: <i>25 KG</i>
 THINNING: <i>Ready to use, does not require thinning.</i>	 DRYING TIME: <i>Drying Time Touch dry (at 23 °C): 4-6 hours *drying time may be longer at higher relative humidity and lower temperature.</i>
 PRIMER: <i>-</i>	 Fully Dry: <i>24 hours</i>
 APPLICATION TOOL: <i>Trowel, sandpaper</i>	 COLORING: <i>-</i>
 NUMBER of COATS: <i>1 or 2</i>	 VOC: <i>Not covered by the EU limit value (Directive 2004/42/EC). ACRYLIC PUTTY INTERIOR: contains a maximum of 31.2 g/l VOC.</i>
 STORAGE and SHELF LIFE: <i>Can be stored for 2 years between +5 °C and +35 °C, in its unopened packaging, in a cool and dry place protected from direct sunlight.</i>	

CONSUMPTION - Single Coat : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.*

 1 L covers 3-5.8 m²,
1 kg covers 1.7-3.3 m².
Paint consumption per 1 m² surface: 170-340 ml
or 300-600 g.

APPLICATION AREA

It is used as an undercoat material for leveling rough concrete and mineral plastered surfaces, and for repairing surface defects formed after removing blistered parts on previously painted surfaces.

SURFACE PREPARATION

After removing all dirt, oil, flaking paint, and dust from the surfaces to be applied, the product should be applied.

SURFACE CONDITIONS

During application and until the products are completely dry, the ambient and surface temperature should be at least +5°C and at most +35°C.

During application, the ambient humidity should be below 75%.

The moisture content of the surface to be applied should be below 10%.

APPLICATION

Acrylic Putty Interior should be mixed homogeneously before application without dilution.

The product is applied with a steel trowel in 1 or 2 coats, depending on the surface roughness.

After waiting 24 hours, surface irregularities and trowel marks should be smoothed by sanding.

HAZARD & PRECAUTIONARY STATEMENTS AND DESCRIPTIONS

- H317: May cause an allergic skin reaction.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P321: Specific treatment (see label).
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).

This technical data sheet is prepared based on laboratory data under normal conditions; for any details not sufficiently covered above, please consult technical personnel. Otherwise, the manufacturer cannot be held responsible for errors arising from insufficient information. Our company reserves the right to change this information. If necessary, detailed information regarding the health, safety, and transportation risks and precautions of the products can be found in the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds conformity certificates for ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.