

AMARSIS PRIMER

Amarsis Primer

AMARSIS PRIMER is a colored primer designed for the Amarsis product. It has two types: Amarsis Dark Primer and Amarsis Light Primer.



It has high opacity.

It adheres perfectly to the surface, providing an ideal base for the Amarsis product to be applied.

It has a textured structure that enhances mechanical adhesion to the surface.

It is water-based, environmentally friendly, and harmless to human health.



CONTENT: Acrylic-based - water-based



PACKAGING: 1 L



THINNING: With 5-10% clean water.



DRYING TIME: Drying Time Touch dry (at 23°C): 2-3 hours
*drying time may be longer at higher relative humidity and lower temperature.



PRIMER: San Deco Amarsis Primer



Fully Dry: 24 hours



APPLICATION TOOL: Roller



COLORING: Amarsis Color Chart



NUMBER of COATS: 1



STORAGE and SHELF LIFE:
Can be stored unopened for 2 years
between +5°C and +35°C in a cool,
dry place protected from direct
sunlight.



VOC:
EU limit value (Directive 2004/42/EC)
Category A/I: Decorative effect coatings (water-
based): 200 g/L (2010)
AMARSIS PRIMER: contains max. 31.8 g/L VOC

CONSUMPTION - Single Coat : Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.



1 L covers 12,5-15,5 m²,
1 kg covers 7,9-9,8 m².

Paint consumption per 1 m²: 165-80 ml and 100-125 g.

APPLICATION AREA

It can be applied to all types of mineral surfaces such as concrete, aerated concrete, pressed brick, fine plaster, and gypsum plaster.

SURFACE PREPARATION

All dirt, oil, loose paints, and dust must be removed from the surfaces to be applied. Surface defects should be repaired with San Deco Acrylic Putty Fine.

SURFACE CONDITIONS

During application and until complete drying, ambient and surface temperatures should be between +5°C and +35°C.

Ambient humidity should be below 75% during application.

Surface moisture content should be below 10% before application.

APPLICATION

Amarsis Primer should be thinned with 5-10% clean water by volume and mixed homogeneously before application.

Apply a single coat with a roller.

HAZARD & PRECAUTIONARY STATEMENTS AND EXPLANATIONS

- H317: May cause an allergic skin reaction.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash before reuse.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P321: Specific treatment required (see label).
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).

This technical data sheet is prepared based on laboratory data under normal conditions. For details not found sufficient above, consult technical staff. The manufacturer cannot be held responsible for errors arising from lack of information. The company reserves the right to make changes to this information. For detailed information regarding the health, safety, and transportation risks and precautions of the products, refer to the Material Safety Data Sheet.

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds conformity certificates for ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.