


# AMARSIS

## Decorative Paint with Antique Metal Effect

AMARSIS is a decorative paint developed for interior use, offering an antique metallic effect.



*Its metallic and textured structure creates a modern and elegant appearance in interiors.*

*Thanks to its granular texture and toning effect, it effectively conceals surface imperfections on uneven walls.*

*It is water-based, environmentally friendly, and safe for human health.*

<b>CONTENT:</b> <i>Acrylic-based - water-based</i>	<b>PACKAGING:</b> 2,5 L
<b>THINNING:</b> <i>Ready to use, do not dilute.</i>	<b>DRYING TIME:</b> <i>Drying Time Touch dry (at 23°C): 4-6 hours</i> <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
<b>PRIMER:</b> <i>San Deco Amarsis Primer</i>	<b>Fully Dry:</b> 24-48 hours
<b>APPLICATION TOOL:</b> <i>Brush, trowel</i>	<b>COLORING:</b> <i>Amarsis Color Chart</i>
<b>NUMBER of COATS:</b> 2	<b>VOC:</b> <i>Limit value (Directive 2004/42/EC)</i> <i>Category A/I: Decorative effect coatings (water-based): 200 g/L (2010)</i> <i>AMARSIS: contains max. 24 g/L VOC</i>
<b>STORAGE and SHELF LIFE:</b> <i>Can be stored unopened for up to 1 year in a cool, dry place, protected from direct sunlight, between +5°C and +35°C.</i>	

**CONSUMPTION - Single Coat :** *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.*



1 L covers 4,9-6 m²,

1 kg covers 4,7-5,8 m².

Paint consumption per 1 m²: 165-205 ml and 170-210 g.

## APPLICATION AREA

It is suitable for interior surfaces such as walls, plaster, exposed concrete, and wood, following proper surface preparation and the application of its specific primer.

## SURFACE PREPARATION

All types of dirt, oil, flaking paint, and dust must be thoroughly cleaned from the surface before application. Surface imperfections should be repaired using San Deco Acrylic Putty Fine, followed by priming with San Deco Decoprimer.

## SURFACE CONDITIONS

During application and until the product is completely dry, ensure the ambient and surface temperature is between +5°C and +35°C.

The relative humidity of the environment should be below 75%, and the surface moisture should be below 10%.

## APPLICATION

AMARSIS can be applied using either a brush or a trowel.

For Brush Application: Mix the product slowly and gently with a spatula without dilution. Apply one coat using a brush. After approximately 25 minutes, smooth the surface with a steel trowel. After 4-5 hours, apply the second coat with a brush. About 1 hour after this application, press the surface with a steel trowel to crush and reduce the size of the colored particles. This process creates light and dark tonal variations.

For Trowel Application: Apply the first coat with a trowel without dilution. After 4-5 hours, apply the second coat with the same method. About 1 hour later, press the surface with a steel trowel to crush and reduce the colored particles, creating the characteristic light and dark tones.

For more detailed information, product application videos can be viewed.

If multiple batch numbers are used within the same project, mix them evenly before application to prevent color variations.

Local retouching is not recommended. In cases requiring touch-up, it is advised to reapply the product to the entire affected surface.

## HAZARD & PRECAUTIONARY STATEMENTS

- H317: May cause an allergic skin reaction.  
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.  
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364: Take off contaminated clothing and wash before reuse.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P321: Specific treatment (see label).  
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, refer to the product's Safety Data Sheet (SDS).

This technical data sheet is based on laboratory data obtained under standard conditions. For further details not covered here, please consult technical personnel. Otherwise, any errors arising from insufficient information are not the manufacturer's responsibility. The right to revise this information is reserved by our company. For detailed information on health, safety, transport risks, and precautions, please refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds certifications compliant with ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.