



## Decorative Paints and Coatings

# Atracto/Atracto Touch

### DESCRIPTION

ATRACTO is an acrylic emulsion based silky touch, silver and gold pearlescent finished metallic decorative coating.

ATRACTO TOUCH is silicone added, wipe-clean and has silky matte texture.

### APPLICATION AREA

On all interior walls, plaster coating, gross concrete and wooden surfaces; it is used together with its appropriate primer after the surface preparation.

### PRODUCT FEATURES

- Atracto gives a bright and decorative appearance thanks to the metallic pigments it contains.
- The vivid and bright pigments create a glamorous shine on the surface.
- Its high water vapor permeability allows water vapor to be expelled, enabling the surface to breathe.
- It is water-based and does not harm human health or the environment.
- Its perfumed feature provides a pleasant smell during application.

### SURFACE PREPARATION

After removing all kinds of dirt, grease, bloated paint and dust from the application surface, the surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and undercoated with SAN DECO DECOPRIMER.

### APPLICATION INSTRUCTIONS

- ATRACTO/ATRACTO TOUCH should be mixed homogenously, without dilution.
- At first coat, ATRACTO/ATRACTO TOUCH should be applied by steel trowel or brush. The second coat can be completed by using a towel or brush again by giving desired effect.
- Minimum 6 hours should be allowed between each coat.
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

### DRYING TIME

Allow 5-6 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

### THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

#### ATRACTO:

- 1 lt covers 8,0 – 12,5 m<sup>2</sup> of surface
- 1 kg covers 6,5 – 10,0 m<sup>2</sup> of surface
- The paint consumption for 1 m<sup>2</sup> area is 80-125 ml and 100-150 gr.

#### ATRACTO TOUCH:

- 1 lt covers 8,5 – 13 m<sup>2</sup> of surface
- 1 kg covers 7 – 11 m<sup>2</sup> of surface
- The paint consumption for 1 m<sup>2</sup> area is 76-118 ml and 90-140 gr.

### DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

# Atracto/Atracto Touch

## STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

## HAZARD STATEMENTS

**H317** May cause an allergic skin reaction.

## PRECAUTIONARY STATEMENTS

**P261** Avoid breathing dust/fume/gas/mist/vapours/spray.

**P272** Contaminated work clothing should not be allowed out of the workplace.

**P280** Wear protective gloves/protective clothing/eye protection/face protection.

**P302 + P352** IF ON SKIN: Wash with plenty of soap and water.

**P333 + P313** If skin irritation or rash occurs: Get medical advice/attention.

**P363** Wash contaminated clothing before reuse.

**EUH208** Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)  
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product



### Product Technical Data Sheet No. DP.002.ENG - Rev01 November 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

**This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.**

**DEKA BOYA SANAYİ ve TİC. A.Ş.**

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56  
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88