

ATRACTO / ATRACTO TOUCH

Silky Textured Metallic Pearl Effect Decorative Coating

ATRACTO/ATRACTO TOUCH is a pearlescent, silky decorative coating developed for interior spaces, containing gold and silver metallic pigments. Compared to the ATRACTO product, ATRACTO TOUCH has a more matte appearance and is washable.



Atracto Touch is washable and water-repellent due to its silicone additive.

Atracto/Atracto Touch is water-based, environmentally friendly, and safe for human health.



CONTENT: Acrylic-based - water-based
Atracto Touch: Acrylic-based - water-based - silicone additive



PACKAGING: 1 L ; 2,5 L ; 15 L



THINNING: Ready to use, do not dilute.



DRYING TIME: Drying Time Touch dry (at 23 °C): 5-6 hours
**drying time may be longer at higher relative humidity and lower temperature.*



PRIMER: San Deco Decoprimer



Fully Dry: 24 hours



APPLICATION TOOL: Steel trowel or sponge



COLORING: Atracto Color Chart



NUMBER of COATS: 2



STORAGE and SHELF LIFE:
Can be stored for 2 years in unopened packaging, in a cool and dry place, protected from direct sunlight, between +5 °C and +35 °C.



VOC:
Limit value EU (Directive 2004/42/EC)
Category A/I: Decorative effect coatings (water-based): 200 g/l (2010)
ATRACTO: contains a maximum of 36 g/l VOC
ATRACTO TOUCH: contains a maximum of 48.8 g/l VOC

CONSUMPTION - Two Coats : Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.



Atracto:
1 L covers 5,9-7,3 m²,
1 kg covers 4,9-6 m² of area.
Paint consumption for 1 m² of surface is 135-170 ml and 165-205 g.

Atracto Touch:
1 L covers 5,9-7,3 m²,
1 kg covers 4,9-6 m² of area.
Paint consumption for 1 m² of surface is 135-170 ml and 165-205 g.

APPLICATION AREA

It should be used with its own primer on walls, plaster, exposed concrete, and wooden surfaces of interior spaces after proper surface preparation.

SURFACE PREPARATION

After removing all kinds of dirt, oil, blistered paint, and dust from the surfaces to be applied, surface defects should be repaired with San Deco Acrylic Putty Fine, and then the surface should be primed with San Deco Decoprimer.

SURFACE CONDITIONS

During application and until the product is fully dry, the ambient and surface temperature should be at least +5°C and at most +35°C.

The ambient humidity during application should be below 75%.

The surface moisture value of the area to be applied should be below 10%.

APPLICATION

Atracto/Atracto Touch should be applied in two (2) coats without thinning, after mixing homogeneously.

The first coat is applied with a trowel or sponge.

In the second coat application, circular movements with a trowel are made to achieve the desired appearance. At least 6 hours should be waited between coats.

For more detailed information about the application, product application videos can be viewed.

If more than one batch number is used in the same project, to prevent batch-based differences, it is recommended to mix the batches in equal proportions before application.

Local touch-up is not recommended. In cases requiring touch-up, it is recommended to reapply the product on the entire damaged surface.

HAZARD & PRECAUTIONARY STATEMENTS AND EXPLANATIONS

H317: May cause an allergic skin reaction.

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment (see label).

P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, refer to the product's Safety Data Sheet (SDS).

Since this technical data sheet is prepared based on laboratory data under normal conditions, for further details not sufficiently covered above, consult technical personnel. Otherwise, errors resulting from insufficient information will not impose liability on the manufacturer. The right to modify this information is reserved by our company. If necessary, detailed information about the product's health, safety, transport risks, and precautions can be found in the Material Safety Data Sheet.

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 certification.