

# COMETA

## Acrylic-Based Decorative Paint with Flake Particles

COMETA is a decorative paint developed for interior spaces containing flakes that create a distinctive textured finish.



*It is easy to apply and provides an antique appearance on the applied surface.*

*Its particulate structure and tonal effect help conceal surface imperfections.*

*It is water-based, environmentally friendly, and safe for human health.*

 <b>CONTENT:</b> Acrylic-based - water-based - flake textured	 <b>PACKAGING:</b> 2,5 L
 <b>THINNING:</b> Ready to use, do not dilute.	 <b>DRYING TIME:</b> Drying Time Touch dry (at 23°C): 4-5 hours <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
 <b>PRIMER:</b> San Deco Decoprimer	 <b>Fully Dry:</b> 24 hours
 <b>APPLICATION TOOL:</b> Brush, spatula	 <b>COLORING:</b> Cometa Color Chart
 <b>NUMBER of COATS:</b> 1	 <b>VOC:</b> Limit value EU (Directive 2004/42/EC) Category A/I: Decorative effect coatings (water-based): 200 g/l (2010) COMETA contains a maximum of 21.7 g/l VOC.
 <b>STORAGE and SHELF LIFE:</b> Can be stored unopened in a cool, dry place protected from direct sunlight between +5°C and +35°C for 1 year.	

**CONSUMPTION** - Single Coat : Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.



1 L covers 3,9-4,75 m<sup>2</sup>,  
1 kg covers 3,75-4,6 m<sup>2</sup>.  
Paint consumption per 1 m<sup>2</sup>: 210-260 ml and 215-270 g.

## APPLICATION AREA

It is suitable for use on interior walls, plaster, exposed concrete, and wooden surfaces after proper surface preparation with its specific primer.

## SURFACE PREPARATION

All dirt, oil, loose paint, and dust should be removed from the application surface.

Surface imperfections should be repaired with San Deco Acrylic Putty Fine, and then primed with San Deco Decoprimer.

## SURFACE CONDITIONS

During application and until the product is fully dry, ensure the ambient and surface temperature is between +5°C and +35°C.

Avoid application under direct sunlight.

Ensure the ambient humidity is below 75% and the surface humidity below 10%.

## APPLICATION

Before application, Cometa should be stirred thoroughly without dilution until homogeneous.

The first coat is applied with a brush. After waiting approximately 25 minutes, the surface is smoothed using a plastic spatula to achieve the desired appearance.

Different decorative effects can be created based on application techniques.

For more detailed application instructions, refer to the product's application videos.

If more than one batch number is used in the same project, mix all batches in equal proportions before application to avoid color variations.

Local touch-ups are not recommended. In case of surface damage, reapplication to the entire area is advised.

## HAZARD & PRECAUTIONARY STATEMENTS

H317: May cause an allergic skin reaction.  
EUH071: Corrosive to the respiratory tract.  
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.  
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364: Take off contaminated clothing and wash it before reuse.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).

This technical data sheet is prepared based on laboratory results under normal conditions. Please consult technical staff for additional information not covered above. The manufacturer is not responsible for errors caused by insufficient information. The right to modify this document is reserved. For further details on product health, safety, transportation risks, and precautions, refer to the Safety Data Sheet.

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified to ISO 9001, ISO 14001, ISO 14064, ISO 45001, ISO 27001 standards.