

DESCRIPTION

COMETA is an acrylic emulsion based ready for use decorative paint system, having a simplicity of application and delicacy of antique look.

APPLICATION AREA

Used on wall, plaster coating, concrete and wood surfaces after surface preparation with the appropriate primer.

PRODUCT FEATURES

- COMETA is a decorative product for interiors, which hides uneven wall surfaces easily due to its particulate structure and toning effect.
- As it is water-based, it is harmless to human health and environment.
- Its perfumed feature provides a pleasant smell during application.

SURFACE PREPARATION

After cleaning the surfaces to be painted from any dirt, oil, peeling paints, and dust, surface imperfections should be corrected using SAN DECO ACRYLIC PUTTY INTERIOR, followed by priming with SAN DECO DECOPRIMER.

After Decoprimer is diluted by volume 20-25% with clean water, it should be applied to the surface with a brush with two layers application. In between layers complete dry condition must be provided.

APPLICATION INSTRUCTIONS

Environment and Surface Conditions

- During and for 24 hours after the application, it should be ensured that the ambient temperature remains between +5°C minimum and +35°C maximum.
- During the application, it should be ensured that the ambient humidity is below 75%.
- Make sure the humidity value of the application surface is lower than 10%.

Application

- After primer completely dried, COMETA is mixed carefully with a spatula and applied by its special brush. After 25 minutes, the desired final look should be given to the surface with a plastic spatula; different decorative effects can be achieved by the technique used.
- For more detailed application guidance, product application videos can be watched.

- In cases where more than one batch is used in the same project, it is recommended that the batches be mixed in equal proportions to prevent batch-based differences.
- Touch-ups are not recommended. In case of necessary repairs, the entire affected wall should be reapplied.

DRYING TIME

The touch dry time at 23°C is 4-5 hours and the complete drying time is 24-48 hours.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

- 1 lt covers 7.5 – 9.5 m² of surface,
- 1 kg covers 6.5 – 8.5 m² of surface,
- The paint consumption for 1 m² area is 100-130 ml and 120 – 155 gr.

STORAGE AND SHELF LIFE

The product can be stored in the original sealed package between +5°C - +35°C temperature for 1 year. Make sure that the product is protected from direct sunlight.

HAZARD STATEMENTS AND EXPLANATIONS

EU Limit Value (Directive 2004/42/EC)

Category A/l: Decorative effect coatings (water-based): 200 g/l (2010)

Maximum contained in COMETA: 21.7 g/l VOC

H317 It can cause allergic skin reactions.

EUH071 Corrosive to the respiratory tract.


PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P280 Wear protective gloves/protective clothing/eye protection/face protection.



Note: For more information, please check the Safety Data Sheet (SDS) of the product

This technical data sheet is prepared based on laboratory data under normal conditions. For additional details, consult technical personnel. The manufacturer is not liable for issues arising from incomplete information. The company reserves the right to modify the data. For detailed information on health, safety, and transportation risks, refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified to TS EN ISO 9001, TS EN ISO 14001, and TS 18001 standards.