

DECOPIA

Prismatic Pearl-Effect Topcoat Paint












DECOPIA is a decorative protective interior topcoat paint consisting of a mixture of special prismatic pearlescent glitters with a three-dimensional effect.



Thanks to its special prismatic pearls, three different colors can be observed depending on the light and viewing angle.

It has a wipeable surface.

It is water-based, friendly to human health and the environment.

 CONTENT: <i>Acrylic-based – water-based</i>	 PACKAGING: <i>0,5 L ; 1 L</i>
 THINNING: <i>With 3-5% clean water</i>	 DRYING TIME: <i>Drying Time Touch dry (at 23°C): 2-3 hours</i> <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
 PRIMER: <i>Uniprimer - Decoplas</i>	 Fully Dry: <i>24 hours</i>
 APPLICATION TOOL: <i>Roller, brush</i>	 COLORING: <i>-</i>
 NUMBER of COATS: <i>1</i>	 VOC: <i>Limit value EU (Directive 2004/42/EC)</i> <i>Category A/I: Decorative effect coatings (water-based): 200 g/l (2010)</i> <i>DECOPIA contains a maximum of 46.7 g/l VOC.</i>
 STORAGE and SHELF LIFE: <i>Can be stored for 2 years between +5°C and +35°C, in its unopened packaging, in a cool and dry place protected from direct sunlight.</i>	

CONSUMPTION - Single Coat : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.*



1 L covers 16.5-20 m²,
1 kg covers 16.5-20 m².

Paint consumption per 1 m² surface: 50-60 ml or 50-60 g.

APPLICATION AREA

It is used decoratively and protectively on various surfaces such as old and newly painted surfaces, wood, wall, drywall, chipboard, cement board, and satin plaster.

SURFACE PREPARATION

All dirt, oil, flaking paint, and dust should be removed from the surface before application.

Surface imperfections should be repaired with San Deco Acrylic Putty Fine and then primed with San Deco Uniprimer.

It is recommended to use the Decoplas product in a color suitable for the chosen Decopia shade as a base coat.

SURFACE CONDITIONS

During application and until the products are completely dry, the ambient and surface temperature should be at least +5°C and at most +35°C.

During application, ambient humidity should be below 75%.

The surface moisture content should be below 10%.

APPLICATION

Decopia should be diluted with clean water up to 3-5% and mixed homogeneously.

The product is applied in a single coat using a brush or roller.

For more detailed application information, product application videos may be watched.

If more than one batch number is used in the same project, to prevent batch-based differences, it is recommended to mix the batches in equal proportions before application.

Local retouching is not recommended. In cases requiring repair, it is advised to reapply the product to the entire affected surface.

HAZARD & PRECAUTIONARY STATEMENTS AND DESCRIPTIONS

- H317: May cause an allergic skin reaction.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P321: Specific treatment (see label).
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).

This technical data sheet is prepared based on laboratory data under normal conditions; for any details not sufficiently covered above, please consult technical personnel. Otherwise, the manufacturer cannot be held responsible for errors arising from insufficient information. Our company reserves the right to change this information. If necessary, detailed information regarding the health, safety, and transportation risks and precautions of the products can be found in the Material Safety Data Sheet (MSDS)

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds conformity certificates for ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.