


# DECOPLAS

## Silicone-Based Waterborne Matte Interior Paint

DECOPLAS is a silicone-based matte decorative interior paint developed for indoor use



*Has wipeable properties.*

*High coverage.*

*Excellent adhesion to the surface.*

*Water-based, environmentally friendly, and harmless to human health.*



**CONTENT:** Acrylic-based - waterborne - silicone-added



**PACKAGING:** 2,5 L ; 7,5 L ; 13,5 L ; 15 L



**THINNING:** With a maximum of 15% clean water.



**DRYING TIME:** Drying Time Touch dry (at 23°C): 4-5 hours  
\*drying time may be longer at higher relative humidity and lower temperature.



**PRIMER:** San Deco Uniprimer



**Fully Dry:** 24 hours



**APPLICATION TOOL:** Roller, brush, spray



**COLORING:** Vision, RAL, NCS



**NUMBER of COATS:** 2



**STORAGE and SHELF LIFE:**  
Can be stored for 2 years between +5°C and +35°C, in its unopened packaging, in a cool and dry place protected from direct sunlight.



**VOC:**  
EU limit value (Directive 2004/42/EC)  
Category A/A: Interior matte wall and ceiling paints (water-based): 30 g/l (2010)  
DECOPLAS: contains a maximum of 30 g/l VOC.

**CONSUMPTION - Single Coat :** Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.



1 L covers 12.5-16 m<sup>2</sup>,  
1 kg covers 8-9.5 m<sup>2</sup>.  
Paint consumption per 1 m<sup>2</sup> area: 65-80 ml or 105-125 g.

### APPLICATION AREA

It is applied on properly prepared mineral surfaces such as rough plaster, concrete, cement board, gypsum panel, and previously painted surfaces together with the appropriate primer.

### SURFACE PREPARATION

All dirt, oil, flaking paint, and dust should be removed from the surface before application.

Surface imperfections should be repaired with San Deco Acrylic Putty Fine and then primed with San Deco Uniprimer.

It is recommended to use a primer of the same color as the selected wall color.

### SURFACE CONDITIONS

During application and until the product is fully dry, ensure that the ambient and surface temperature is between +5°C and +35°C.

The ambient humidity should be below 75%.

The surface moisture content should be below 10%..

### APPLICATION

Before application, Decoplas should be diluted with a maximum of 15% clean water by volume and mixed until homogeneous.

The product is applied to the surface in two (2) coats using a roller, brush, or spray method.

Allow at least 4 hours between coats.

If multiple batch numbers are used in the same project, to prevent batch-related color differences, it is recommended to mix batches in equal proportions before application.

### HAZARD & PRECAUTIONARY STATEMENTS AND DESCRIPTIONS

- H317: May cause an allergic skin reaction.  
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.  
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364: Take off contaminated clothing and wash it before reuse.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P321: Specific treatment (see label).  
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).



Complies with TS 5808/2012.



Complies with G Directive.

This technical data sheet is prepared based on laboratory data under normal conditions; for details not specified above, please consult technical personnel. Otherwise, the manufacturer cannot be held responsible for errors arising from lack of information. Our company reserves the right to make changes to this information. If necessary, you can access detailed information about the product's health, safety, and transportation risks and precautions from the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified to ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.