

DECORATIVE FINISH GLITTER

Glitter-Effect Decorative Transparent Topcoat Paint

DECORATIVE FINISH GLITTER is a decorative topcoat paint that can be applied over decorative putties, paints, and decorative products with a paste-like consistency, creating a glittering appearance.




Easy to apply and does not alter the texture or pattern of the product it is applied over.

Has wipeable properties.

It is water-based, friendly to human health and the environment.

i CONTENT: Acrylic-based - water-based	PACKAGING: 1 L
THINNING: Ready to use or with 30-40% clean water	DRYING TIME: Drying Time Touch dry (at 23°C): 2-3 hours *drying time may be longer at higher relative humidity and lower temperature.
PRIMER: San Deco Decoprimer	Fully Dry: 24 hours
APPLICATION TOOL: Brush, roller, sponge	COLORING: -
NUMBER of COATS: 1	√ voc:
STORAGE and SHELF LIFE: Can be stored for 2 years between +5°C and +35°C, in its unopened packaging, in a cool and dry place protected from direct sunlight.	V Limit value EU (Directive 2004/42/EC) Category A/I: Decorative effect coatings (waterbased): 200 g/I (2010) DECORATIVE FINISH GLITTER: contains a maximum of 48 g/I VOC.

CONSUMPTION - Single Coat : Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.





UYGULAMA ALANI APPLICATION AREA

It is applied as a topcoat material on decorative products used on walls, plaster, fair-faced concrete, and wooden surfaces after surface preparation.

SURFACE CONDITIONS

During application and until the products are completely dry, the ambient and surface temperature should be at least +5°C and at most +35°C.

During application, ambient humidity should be below 75%.

The surface moisture content should be below 10%.

APPLICATION

Decorative Finish Glitter should be applied with a brush directly over decorative putty and other paste-like decorative products without dilution.

For painted surfaces, it should be diluted with 30-40% clean water by volume and mixed homogeneously before application.

It is applied to the surface in a single coat using a brush, sponge, or roller.

If more than one batch number is used in the same project, to prevent batch-based differences, it is recommended to mix the batches in equal proportions before application.

Local retouching is not recommended. In cases requiring repair, it is advised to reapply the product to the entire affected surface.

HAZARD & PRECAUTIONARY STATEMENTS AND DESCRIPTIONS

H317: May cause an allergic skin reaction.

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment (see label).

P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).

This technical data sheet is prepared based on laboratory data under normal conditions; for any details not sufficiently covered above, please consult technical personnel. Otherwise, the manufacturer cannot be held responsible for errors arising from insufficient information. Our company reserves the right to change this information. If necessary, detailed information regarding the health, safety, and transportation risks and precautions of the products can be found in the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds conformity certificates for ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.