

DESCRIPTION

DECOSTUCCO is an acrylic emulsion based; containing various types of quartz, limestone and pigments; at the paste consistency; given texture and form with trowel or spatula; glossy finished interior wall coating material.

APPLICATION AREA

Used after surface preparation with the appropriate primer on wall, plaster coating, concrete and wood surfaces.

PRODUCT FEATURES

- Decostucco creates a marble effect on the applied surface.
- Its high brightness creates vivid and shiny colors on the applied surface.
- Its high water vapor permeability allows water vapor to be expelled, enabling the surface to breathe.
- It is water-based and does not harm human health or the environment.

SURFACE PREPARATION

After cleaning the surfaces to be painted from any dirt, oil, peeling paints, and dust, surface imperfections should be corrected using SAN DECO ACRYLIC PUTTY INTERIOR, followed by priming with SAN DECO DECOPRIMER.

APPLICATION INSTRUCTIONS

Environment and Surface Conditions

- During and for 24 hours after the application, it should be ensured that the ambient temperature remains between +5°C minimum and +35°C maximum.
- During the application, it should be ensured that the ambient humidity is below 75%.
- Make sure the humidity value of the application surface is lower than 10%

Application

- DECOSTUCCO should well mixed before application
- One layer DECOSTUCCO is applied to the surface with a stainless steel trowel, the second coat is applied if the desired smoothness and coverage is not obtained.
- Once the product is dried after 24 hours, the surface is sanded with fine sandpaper and the desired effect is applied by trowel or spatula. To make the surface more glossy, steel trowel work can be done over again.

- For more detailed application guidance, product application videos can be watched.
- In cases where more than one batch is used in the same project, it is recommended that the batches be mixed in equal proportions to prevent batch-based differences.
- Touch-ups are not recommended. In case of necessary repairs, the entire affected wall should be reapplied.

DRYING TIME

The touch dry time at 23°C is 2-3 hours and the complete drying time is 24 hours.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

- 1 lt covers 2.85 – 4.30 m² of surface
- 1 kg covers 1.65 – 2.5 m² of surface
- The paint consumption for 1 m² area is 230 – 350 ml and 400 – 600 gr

STORAGE AND SHELF LIFE

The product can be stored in the original sealed package between +5°C - +35°C temperature for 2 year. Make sure that the product is protected from direct sunlight.

HAZARD STATEMENTS AND EXPLANATIONS

EU Limit Value (Directive 2004/42/EC)

Category A/I: Decorative effect coatings (water-based): 200 g/l (2010)

Maximum contained in DECOSTUCCO: 48,6 g/l VOC

H317 It can cause allergic skin reactions.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment (see...on this label)

P272: Contaminated work clothing should not be allowed out of the workplace.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88

Note: For more information, please check the Safety Data Sheet (SDS) of the product.

This technical data sheet is prepared based on laboratory data under normal conditions. For additional details, consult technical personnel. The manufacturer is not liable for issues arising from incomplete information. The company reserves the right to modify the data. For detailed information on health, safety, and transportation risks, refer to the Material Safety Data Sheet (MSDS). This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified to TS EN ISO 9001, TS EN ISO 14001, and TS 18001 standards