



Decorative Paints and Coatings

Effect Wind (2X)

DESCRIPTION

EFFECT WIND is an acrylic emulsion based decorative interior paint, characterized with its special grain structure and two dimensional pearl effects.

APPLICATION AREA

Can be used as an interior coating for the walls, roofs, gross concrete and wooden surfaces and all kinds of new or old painted surfaces.

FEATURES

- Creates difference on the surfaces of applications by its special grain texture and two dimensional pearls
- By emphasizing the grain structure in the product; different applications can be achieved
- Due its high vapor permeability, it allows surface to discharge the steam and breathe
- As it is water-based, it is harmless to human health and environment
- It provides a pleasant odour in the application environments with its perfumed feature.

SURFACE PREPARATION

After removing all kinds of dirt, grease, bloated paint and dust from the application surface, the surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and undercoated with SAN DECO UNIPRIMER.

APPLICATION INSTRUCTIONS

- EFFECT WIND is a product, which is applied on the EFFECT WIND UNDERCOAT. Effect Wind Undercoat which chosen according to color chart, should be thinned with 5-10% clean water and be applied with 2 layer, using roller or brush. 4-5 hours should be allowed between each coat.
- EFFECT WIND is applied with a special application tool consisting of dual headed brushes after drying of Effect Wind Undercoat. Dual headed brushes dived into the Effect Wind packages, which are chosen two different colors. The application technique is based on applying the product in all directions on the wall without overlapping two colors with alternative brush touches. Before the product starts drying, the grain particles inside will be spread by wooden brush applying cross touches.
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

DRYING TIME

Allow 4-5 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

- 1,2 (0,6 lt+0,6lt) lt covers 10,0 – 12 m² of surface
- 1 kg covers 7-8,5 m² of surface
- The paint consumption for 1 m² area is 100-120 ml and 110-140 gr.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

Effect Wind (2X)

STORAGE

It should be stored in a sealed package, cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product



Product Technical Data Sheet No. DP.005.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88