

Nostalgie Finish

DESCRIPTION

NOSTALGIE FINISH is an acrylic-based emulsion; a decorative and transparent paint for interior.

APPLICATION AREA

It can be applied on interior walls of buildings, plaster, concrete and wood surfaces after surface preparation. The product is used together with NOSTALGIE BASE product.

FEATURES

- It highlights antique effects to the surface
- It gives a velvety texture
- Due its high vapor permeability, it allows surface to discharge the steam and breathe
- As it is water-based, it is harmless to human health and environment
- It provides a pleasant odor in the application environments with its perfumed feature.

SURFACE PREPARATION

- Before application, NOSTALGIA BASE should be mixed without dilution.
- Use a steel or a plastic trowel to apply NOSTALGIE BASE on the wall, according to the desired effect, without regularity.

APPLICATION INSTRUCTIONS

- Two days after having applied NOSTALGIE BASE on the surface, NOSTALGIE FINISH should be applied in a circular motion and by using a special fabric or glove.
- The color tones can be arranged while applying NOSTALGIE FINISH, according to desired aspect, by applying a thin or a thick coat.
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

DRYING TIME

Allow 4-5 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

- -1 lt covers 10,6-14,7 m² of surface
- -1 kg covers $9.0 12.5 \text{ m}^2$ of surface
- -The paint consumption for 1 m² area is 70-90 ml and 80-110 gr.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight and at a temperature between $+5^{\circ}$ C and $+35^{\circ}$ C.



Nostalgie Finish

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. DP.015.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.