



## Decorative Paints and Coatings

# Obiante

### DESCRIPTION

It is a decorative coating material of natural lime based consisting of a mixture of different sized particles of marble powder and natural minerals, used for indoor surfaces.

### APPLICATION AREA

OBIANTE provides depth and character to all kinds of indoor walls, plaster, gross concrete and timber surfaces following surface preparation with suitable plaster and pearlescent final coat solution.

### FEATURES

- Easy to apply.
- It has an excellent filling capacity. Applied as a single coat.
- Its water permeability is excellent and thanks to this property, it allows the product to breathe.
- Thanks to its natural lime content, it is naturally resistant against bacteria and mold.
- Water based.

### SURFACE PREPARATION

After cleaning all kinds of dust, dirt, oil, swelled paint from the application area, surface irregularities should be eliminated by SAN DECO ACRYLIC PUTTY INTERIOR and should be plastered with SAN DECO DECOPRIMER.

### APPLICATION INSTRUCTIONS

- Before application, OBIANTE should be softened by mixing with steel hoe without diluting.
- Then OBIANTE is applied on surface as a single coat according to the desired thickness with a steel hoe.  
Various designs are formed with a special tool while the product is still wet.
- After 20 minutes at 23±2°C, when product starts to settle, the surface is finished by furbishing it with a steel trowel. In order to ensure a better smoothness and brightness, the surface of the product is thoroughly smoothed with trowel after spraying water on OBIANTE product. Then let it drying.
- After complete dryness is reached with OBIANTE product, Pearlescent Decorative Finish is applied in one or more color as desired to complete the procedure.
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

### DRYING TIME

Allow 5-6 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

### THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application;

-1 lt covers 1,05 – 1,40 m<sup>2</sup> of surface

-1 kg covers 0,65 – 0,85 m<sup>2</sup> of surface

-The paint consumption for 1 m<sup>2</sup> area is 715 – 950 ml and 1200 – 1600 gr.

### STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight and at a temperature between +5°C and +35°C.

### DEKA BOYA SANAYİ ve TİC. A.Ş.



## Decorative Paints and Coatings

# Obiante

### HAZARD STATEMENTS

**H315** Causes skin irritation.

**H318** Causes serious eye damage.

**H335** May cause respiratory irritation.

### WARNINGS/ PRECAUTIONS

**P261** Avoid breathing dust/fume/gas/mist/vapours/spray.

**P264** Wash with water thoroughly after handling

**P280** Wear protective gloves/protective clothing/eye protection/face protection

**P302+P352** Wash with plenty of water in contact with skin

**P304+P340** IF INHALED: Remove person to fresh air and keep comfortable for breathing

**P305+P351+P338** IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. continue rinsing

**P332+P313** If skin irritation occurs: Get medical advice/attention.

**P362** Take off contaminated clothing

Note: For more information, please check the Safety Data Sheet (SDS) of the product

**DEKA BOYA SANAYİ ve TİC. A.Ş.**

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56  
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88