



Decorative Paints and Coatings

Mirzasto

DESCRIPTION

MIRZASTO is an easy to apply acrylic-based emulsion decorative coating. It enables to give pattern with its putty consistency through your walls in order to achieve elegant look.

APPLICATION AREA

MIRZASTO is applied on interior walls, plaster, exposed concrete and wooden surfaces after the surface preparation with a suitable primer. It is used with the final coat product EFFECT FINISH.

FEATURES

- It can be applied easily as it has special fillings inside
- The pattern and sanding can be done easily
- Due its high vapor permeability, it allows surface to discharge the steam and breathe
- On MIRZASTO application, there should not be any problem of early drying as the product features don't allow this
- As it is water-based, it is harmless to human health and environment.

SURFACE PREPARATION

The application surface must be cleaned out from every kind of dirt, stain, swelled paint and dust and then uneven surface must be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and primed with SAN DECO DECOPRIMER.

APPLICATION INSTRUCTIONS

- MIRZASTO should be mixed homogeneously without thinning.
- MIRZASTO should be spread with a steel spud, slowly on 1-2 m² area. Then, according to the desired decorative effect, with a plastic or a steel spud, apply the product with untidy patterns. Before MIRZASTO dries, smooth and striped patterns can be applied again with a steel or a plastic spud.
- Wait 4 hours at a temperature of 23°C, (220/260) then use a grained sanding paper to wipe out the untidy bumps.
Finally, according to colour catalogue, first colored EFFECT FINISH can be applied one after the other(Wait 3 hours between EFFECT FINISH coats)
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

DRYING TIME

Allow 4-5 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

-1 lt covers 4,0 – 5,0 m² of surface

-1 kg covers 2,3 – 2,9 m² of surface

-The paint consumption for 1 m² area is 200 – 250 ml and 350 – 450 gr.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

Mirzasto

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight and at a temperature between +5°C and +35°C.

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product



Product Technical Data Sheet No. DP.022.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88