

Decorative Paints and Coatings Decopia

DESCRIPTION

DECOPIA is an acrylic emulsion base decorative interior final coat finish paint. It consists of prismatic three dimensional pearl and this provides color effects of different looks according to different angle of lights and also gives glittering effect through.

APPLICATION AREA

It can be used for decorative and protective purposes on all kinds of surfaces such as wooden, wall, concrete panels, and satin plaster regardless of old painted or newly painted surfaces.

FEATURES

- Thanks to special prismatic mother of pearls that it includes, 3 different colors can be seen depending on lightening and point of view
- It can be wiped with water.
- Due its high vapor permeability, it allows surface to discharge the steam and breathe
- As it is water-based, it is harmless to human health and environment
- It provides a pleasant odour in the application environments with its perfumed feature.

SURFACE PREPARATION

- After removing all kinds of dirt, grease, bloated paint and dust from the application surface, the surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and undercoated with SAN DECO UNIPRIMER
- It is advised to use SAN DECO Decoplas matt interior paint with desired color on primer applied before.
- Decoplas should be dilueted for 20% in volume with clean water; then applied in two coats with roller or brush without allowing traces. 4 hours should be allowed between each coat.

APPLICATION INSTRUCTIONS

- After undercoat is dried, DECOPIA is applied on surface as one coat with brush or roller by diluting %3-5 with water. Preferred method of application is with special brush application
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

DRYING TIME

Allow 2-3 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

- -1 lt covers $16.5 20.0 \text{ m}^2$ of surface
- -1 kg covers $16.5 20.0 \text{ m}^2$ of surface
- -The paint consumption for 1 m^2 area is 50 60 ml and 50 60 gr.

STORAGE

It should be stored in a sealed package, cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.



Decorative Paints and Coatings Decopia

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product



Product Technical Data Sheet No. DP.025.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.