



Interior Products Range

Beton Contact

DESCRIPTION

BETON CONTACT is an acrylic emulsion based undercoat, developed exclusively to increase the adherence of the gypsum plaster to the surface on exposed concrete and ceilings.

APPLICATION AREA

BETON CONTACT is used to increase the adherence of gypsum plaster and similar lime-gypsum mortars on exposed concrete.

FEATURES

- Adheres very well to the surface,
- Penetrates exposed concrete very well to provide a good ground for other application materials,
- As it is water-based, it is harmless to human health and environment.

SURFACE PREPARATION

Clean all dirt, oil, blistered paint and dust off the application surface; level the surface defects, if any.

APPLICATION INSTRUCTIONS

- Prior to application dilute BETON CONTACT with 40-45% water, mix well.
- Then apply the product with roller,
- Start plaster or gypsum application 24 hours after applying BETON CONTACT.
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

DRYING TIME

Allow 5-6 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application;
 -1 lt covers 5,5 - 11,0 m² of surface,
 -1 kg covers 3,0 - 6,5 m² of surface,
 -The paint consumption for 1 m² area is 90 - 180 ml and 150 - 330 gr.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

H 362 May cause harm to breast-fed children,

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P263 Avoid contact during pregnancy/while nursing.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Interior Products Range

Beton Contact

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. IP.009.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88