

## 1.DESCRPTION

MARMOROSSO MARMORINO is a mineral and natural lime-based, antique marblelooking interior decorative coating.

## 2.APPLICATION AREA

After surface preparation, it can be used on all kinds of walls, plaster, exposed concrete, and wooden surfaces along with a suitable primer. It adds depth and character to the applied surface.

## 3.FEATURES

- It is easy to apply.
- It is applied in two coats, either plain or textured.
- Its exceptional water vapor permeability promotes the elimination of moisture, allowing the surface to breathe.
- It's resistant to bacteria and molds thanks to the natural lime in its content.
- Water-based, making it environmentally friendly and safe for human health.

## 4.SURFACE PREPARATION

After all kinds of dirt, oil, bloated paints, and dust are cleaned from the surfaces, surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and primed with SAN DECO DECOPRIMER.

## 5.APPLICATION INSTRUCTIONS

### 5.1. Environmental and Surface Conditions

- During and for 24 hours after the application, it should be ensured that the ambient temperature remains between +5°C minimum and +35°C maximum.
- Avoid application under direct sunlight.
- Ensure that the ambient humidity is below 75% during the application.
- Make sure that the moisture content of the surface to be applied is below 10%.

### 5.2. Application:

- Before the application, soften the Marmorosso Marmorino by mixing it thoroughly using a spatula or trowel without diluting it.
- Apply the first coat using a steel trowel. Depending on the ambient temperature, the second coat application can be started after 6-8 hours.
- Apply the second coat in a thickness appropriate to the desired texture and pattern.
- In the second coat, distribute the product homogeneously using a steel trowel by pressing in various directions.
- After the product begins to shrink, and depending on the ambient temperature, the wetness on the surface gradually becomes matte. Meanwhile, apply a small amount of product to the surface by pressing it in various directions using a steel trowel until the surface becomes completely homogeneous.
- Then, polish the product using a clean steel trowel. The more the product is polished with a trowel before it dries, the brighter it will become.
- Since the product is natural lime-based, the color of the wet product will lighten by 4 to 5 tones after drying.
- Touch-ups are not recommended. In cases where touch-ups are necessary, it is advised to reapply the entire affected wall for a uniform finish.

## 6. DRYING TIME

The touch dry time at 23°C is 6-8 hours and the complete drying time is 24-48 hours.

## 7. THEORETICAL CONSUMPTION

For flat homogeneous application (2 coats):

- Covers 1.00–1.30 m<sup>2</sup> per liter,
- Covers 0.65–0.85 m<sup>2</sup> per kg,
- Product consumption per 1 m<sup>2</sup>: 765–1015 ml and 1200–1600 g.

For textured application (2 coats):

- Covers 0.65–0.80 m<sup>2</sup> per liter,
- Covers 0.40–0.50 m<sup>2</sup> per kg,
- Product consumption per 1 m<sup>2</sup>: 1275–1590 ml and 2000–2500 g.

## 8. STORAGE AND SHELF LIFE

It can be stored for 1 year in its unopened package, in a cool and dry place, protected from direct sunlight, between +5°C and +35°C.

## 9. HAZARD STATEMENTS

EU limit value (Directive 2004/42/EC)

Category A/I: Decorative effect coatings (water-based): 200 g/l (2010)

MARMOROSSO MARMORINO contains max: 42 g/l VOC

H314 May cause an allergic skin reaction. H314 May cause an allergic skin reaction.

## PRECAUTIONARY STATEMENTS

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P405: Store locked up.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P305+P351+P338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P310: Immediately call a POISON CENTER or doctor/physician.

P264: Wash ... thoroughly after handling.

P321: Specific treatment (see ... on this label).

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Note: For more information, please check the Safety Data Sheet (SDS) of the product.

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health- safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.Ş. who is also certified by the standarts of TS EN ISO 9001, TS EN ISO 14001, TS EN ISO 18001.