

MARMOROSSO MARMORINO

Mineral-Based Decorative Plaster with Antique Marble and Natural Stone Effect












MARMOROSSO MARMORINO is a mineral-based, natural lime-based, antique marble-looking decorative interior wall coating material.




Thanks to its natural lime content, it has natural resistance against bacteria and mold.

Since Marmorosso Marmorino is natural lime-based, after full drying the final color becomes 4-5 tones lighter than the wet paint color.

Allows creation of various patterns and textures.

 CONTENT: <i>Lime-based – water-based</i>	 PACKAGING: <i>10 KG; 20 KG.</i>
 THINNING: <i>Ready to use; do not dilute.</i>	 DRYING TIME: <i>Drying Time Touch dry (at 23 °C): 6-8 hours</i> <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
 PRIMER: <i>San Deco Decoprimer</i>	 Fully Dry: <i>24-48 hours</i>
 APPLICATION TOOL: <i>Steel trowel</i>	 COLORING: <i>Liberte Art Color Chart</i>
 NUMBER of COATS: <i>2</i>	 VOC: <i>EU limit value (Directive 2004/42/EC)</i> <i>Category A/I: Decorative effect coatings (water-based): 200 g/L (2010)</i> <i>MARMOROSSO: contains a maximum of 42 g/L VOC.</i>
 STORAGE and SHELF LIFE: <i>Can be stored unopened for 2 years between +5°C and +35°C in a cool, dry place protected from direct sunlight.</i>	

CONSUMPTION - Two Coats : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.*

 1 L covers 0,9-1,22 m²
1 kg covers 0,55-0,75 m²
For 1 m²: approx. 800-1100 ml; 1350-1850 g.

APLLICATION AREA

Should be used with its own primer on interior walls, plaster, fair-faced concrete, and wooden surfaces after appropriate surface preparation.

SURFACE PREPARATION

All dirt, oil, loose/peeling paints, and dust must be removed from the surface. Surface defects should be repaired with San Deco Acrylic Putty Fine, then primed with San Deco Decoprimer.

SURFACE CONDITONS

During application and until full drying, ambient and substrate temperature must be between +5°C and +35°C.

Ambient humidity must be below 75%.

Substrate moisture must be below 10%.

APPLICATION

Marmorosso Marmorino should be applied without thinning, after mixing homogeneously, using a trowel.

The first coat is applied smoothly with a trowel and allowed to dry for 6-8 hours.

The second coat is applied, with appropriate thickness to achieve the desired texture and decorative effect, using the trowel.

As the product begins to dry, wet-looking areas gradually become matte. At this stage, a small amount of product is taken on the trowel and applied by pressing in various directions. The surface is compressed with the trowel until fully homogeneous.

After this, the surface is burnished/polished using a clean trowel.

The more the surface is burnished before the full drying time is completed, the shinier the finish becomes.

For detailed application guidance, application videos may be viewed.

If more than one batch number is used in the same project, batch differences can be prevented by mixing the batches in equal proportion before application.

HAZARD & PRECAUTIONARY STATEMENTS

H314: Causes severe skin burns and eye damage.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P405: Store locked up.

P260: Do not breathe dust/fume/gas/mist/vapors/spray.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P310: Call the NATIONAL POISON CENTER at 114 or a doctor/physician.

P264: Wash hands thoroughly after handling.

P321: Specific treatment required (see label).

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Note: For more information, please consult the Safety Data Sheet (SDS).

This technical data sheet is based on laboratory results under standard conditions. For additional details not covered here, consult technical personnel. The manufacturer is not responsible for errors arising from insufficient information. The right to make changes is reserved. For detailed information regarding health, safety, and transport risks, refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified to ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001.