

## DESCRIPTION

Marmorosso Marmarino mineral and natural lime based, antique marble look, interior decorative coating material.

# **APPLICATION AREA**

Provides depth and character to all kinds of indoor walls, plaster, gross concrete and timber surfaces following surface preparation with suitable plaster and some topcoat finished.

# FEATURES

- Easy to apply,
- Product can be applied as plain or textured as 2 coats,
- Product's water permeability is excellent and thanks to this property, it allows the product to breathe,
- With its natural lime content, it is naturally resistant against bacteria and mold.
- Water-based

## SURFACE PREPARATION

After cleaning all kinds of dust, dirt, oil, swelled paint from the application area, surface irregularities should be eliminated by SAN DECO Acrylic Putty Interior and should be plastered with SAN DECO DECOPRIMER.

# **APPLICATION INSTRUCTIONS**

- Before application, MARMOROSSO MARMARINO should be softened by mixing homogeneously with steel trowel without diluting.
- Then MARMOROSSO MARMARINO is applied on surface as two coat according to the desired thickness with a trowel. Once first coat is applied, second coat should be carried on after 6-8 hours later.
- Various designs are formed with a special tool on the second coat either plain or different textures. According to the temperature, product moisture disappears while you trowel the products and get more matt. And then product get more firm and tighten.
- And then if the product wants to be glossy, more trowel moves should be applied ever and ever again until it gets desired glossiness.
- After complete dryness is reached with MARMOROSSO MARMARINO product, it might get more light color since it is organic lime based.
- Once application done and fully dryness achieved; by applying San Deco Shield (matte or glossy); product can also be used in indoor humid environments. Odor release may occur in the places with humid and high temperatures caused due to natural lime use. Therefore, it is recommended to apply san deco shield (matte or glossy) on Marmorosso Marmarino in such environments.
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

## DRYING TIME

Allow 6-8 hours for touch dry and 24-48 hours for complete dry at 23°C environment conditions.

## THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for two layers application:

#### DEKA BOYA SANAYİ ve TİC. A.Ş.



Smooth application for two layers;

- 1 It covers 1,00–1,30 m<sup>2</sup>,of surface
- 1 kg covers 0,65–0,85 m<sup>2</sup> of surface
- The paint consumption for 1 m<sup>2</sup> area is 765-1015 ml and 1200-1600 gr.

Textured application for two layers;

- 1 lt covers 0,65-0,85 m<sup>2</sup>,of surface
- 1 kg covers 0,40-0,50 m<sup>2</sup> of surface
- The paint consumption for 1 m<sup>2</sup> area is 1275-1590 ml and 2000-2500 gr.

# STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight at a temperature between +5°C and +35°C.

## HAZARD STATEMENTS

H315 Causes skin irritation.H318 Causes serious eye damage.H335 May cause respiratory irritation.

#### WARNINGS/ PRECAUTIONS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash with water thoroughly after handling
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 Wash with plenty of water in contact with skin
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. continue rinsing
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing

Note: For more information, please check the Safety Data Sheet (SDS) of the product.