

# NOSTALGIE

## *Antique Stone Effect Decorative Coating*

NOSTALGIE is a fiber-reinforced decorative coating developed for interior surfaces.














*Easy to apply; allows creating various textures with different application techniques.*

*When used with Nostalgie Finish, it provides an antique stone appearance by creating a sense of depth on the surface.*

*Thanks to its fiber content, it enables thick-textured applications without cracking.*

*Water-based; environmentally friendly and safe for human health.*

 <b>CONTENT:</b> <i>Acrylic-based, water-based, fiber-reinforced.</i>	 <b>PACKAGING:</b> 10 KG
 <b>THINNING:</b> <i>Ready to use; do not dilute.</i>	 <b>DRYING TIME:</b> <i>Drying Time Touch dry (at 23 °C): 6-8 hours</i> <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
 <b>PRIMER:</b> <i>San Deco Decoprimer</i>	 <b>Fully Dry:</b> 48 hours
 <b>APPLICATION TOOL:</b> <i>Steel trowel</i>	 <b>COLORING:</b> -
 <b>NUMBER of COATS:</b> 1	 <b>VOC:</b> <i>EU Limit Value (Directive 2004/42/EC)</i> <i>Category A/I: Decorative effect coatings (water-based): 200 g/L (2010)</i> <i>NOSTALGIE: Maximum content: 1.25 g/L VOC</i>
 <b>STORAGE and SHELF LIFE:</b> <i>Can be stored unopened for 2 years between +5 °C and +35 °C, in a cool and dry place protected from direct sunlight.</i>	

**CONSUMPTION - Single Coat :** *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.*



1 L covers 0,55-0,8 m<sup>2</sup>

1 kg covers 0,45-0,65 m<sup>2</sup>

For 1 m<sup>2</sup>: approx. 1250-1700 ml and 1500-2100 g.

## APPLICATION AREA

After proper surface preparation, it should be applied with its own primer on interior walls, plaster, exposed concrete, and wooden surfaces.

## SURFACE PREPARATION

All dirt, oil, loose paint, and dust must be cleaned from the application surface. Surface defects must be repaired with San Deco Acrylic Putty Fine and then primed with San Deco Decoprimer.

## SURFACE CONDITIONS

During application and until full curing is completed, surface and ambient temperature must be between +5°C and +35°C.

Ambient humidity should be below 75% during application.

Surface moisture should be below 10%.

## APPLICATION

Nostalgie Base must be mixed homogeneously without thinning prior to application.

Apply the product irregularly with a trowel to achieve the desired effect.

After two (2) days from the Nostalgie Base application, sand the surface to remove roughness. Then apply Nostalgie Finish to the surface using circular motions with a roller. Depending on the desired appearance, apply in thin or thick layers, or adjust tonal variations by wiping with a sponge.

For more detailed application information, product application videos can be viewed.

If more than one batch is used in the same project, mix the batches evenly before application to prevent batch-based differences.

Local touch-ups are not recommended. For retouching needs, it is recommended to reapply the product to the entire damaged area.

## HAZARD & PRECAUTIONARY STATEMENTS

- H317: May cause allergic skin reactions.  
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.  
P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.  
P362 + P364: Take off contaminated clothing and wash it before reuse.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P321: Specific treatment required (see label).  
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: Refer to the Safety Data Sheet (SDS) for more information.

This technical data sheet is prepared based on laboratory results under standard conditions. For details not covered here, consult technical personnel. Otherwise, the manufacturer cannot be held responsible for errors resulting from insufficient information. The right to make changes to this document is reserved. Detailed information regarding health, safety, and transport risks can be found in the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified to ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.