

OBIANTE

Natural Lime-Based and Mineral-Enhanced Decorative Coating

OBIANTE is a natural lime-based decorative coating material consisting of a blend of marble powders of different sizes and natural minerals, designed for use on interior surfaces.














Easy to apply; allows various textures to be created with different application techniques.


Naturally resistant to bacteria and mold due to its lime content.

Highly breathable thanks to its water vapor permeability.

Water-based; environmentally friendly and safe for human health.

 CONTENT: <i>Lime-based - water-based</i>	 PACKAGING: <i>10 KG; 20 KG.</i>
 THINNING: <i>Ready to use; do not dilute.</i>	 DRYING TIME: <i>Drying Time Touch dry (at 23°C): 5-6 hours</i> <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
 PRIMER: <i>San Deco Decoprimer</i>	 Fully Dry: <i>24hours</i>
 APPLICATION TOOL: <i>Trowel</i>	 COLORING: <i>-</i>
 NUMBER of COATS: <i>1</i>	 VOC: <i>EU Limit (Directive 2004/42/EC)</i> <i>Category A/I: Decorative effect coatings (water-based): 200 g/L (2010)</i> <i>OBIANTE maximum VOC content: 43 g/L.</i>
 STORAGE and SHELF LIFE: <i>Unopened packaging may be stored for 2 years at +5°C to +35°C in a cool and dry place protected from direct sunlight.</i>	

CONSUMPTION - Single Coat : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.*

 1 L covers 0,85-1,15 m²
1 kg covers 0,5-0,7 m²
For 1 m²: approx. 850-1150 ml ve 1400-2000 g.