

1. PRODUCT DESCRIPTION

PATINALUSSO is developed to be applied on the acrylic and lime-based products. It has a semi-pearlescent effect and creates a shiny appearance on the applied surface.

PATINALUSSO, which gives the surfaces a decorative touch, has an easy application and is suitable for manual or mechanical polishing.

2. APPLICATION AREA

It is applied to the surfaces of acrylic and lime-based decorative coatings on the interior spaces.

3. PRODUCT FEATURES

- PATINALUSSO, increases the brightness of the applied surfaces.
- It creates an extra soft texture on surfaces thanks to its special wax structure in its content.
- It is easy to apply.
- It creates shiny surfaces with silver and gold finishes.
- It can be easily polished with a dry and clean cloth or a polishing machine.
- It is water-based and has no harm human health or the environment.
- It gives a pleasant smell thanks to its special components.

4. SURFACE PREPARATION

After cleaning all kinds of dirt, grease, oil, and dust, from the surface, you can start the application.

5. APPLICATION INSTRUCTIONS

5.1. Environment and surface conditions.

During and for 24 hours after the application, it should be ensured that the ambient temperature remains between +5°C minimum and +35°C maximum.

During the application, it should be ensured that the ambient humidity is below 75%.

Make sure the humidity value of the application surface is lower than 10%.

5.2. Application:

PATINALUSSO is applied as a thin layer with a steel trowel, in a single coat.

It should be mixed homogeneously without diluting.

After drying, PATINALUSSO is polished with a clean dry cloth or a polishing machine.

After the appropriate drying time, the second coat is applied with a trowel, and the desired pattern is created using a trowel.

If desired, application can also be made using a brush for different textures and patterns.

6.DRYING TIME

At 23°C and 50% humidity, the touch-drying time is 1-2 hours, and the complete drying time is 24 hours.

7.THEORETICAL CONSUMPTION

For single-layer applications depending on surface smoothness, absorbency, and application techniques;

- 1 lt covers an area of 16 – 20 m²,
- 1 kg covers an area of 15 – 19 m².
- Paint consumption per 1 m² is 50 - 60 ml and 52- 62 gr.

8.STORAGE AND SHELF LIFE

The product can be stored in the original sealed package between +5°C - +35°C temperature for 2 years.

9. HAZARD STATEMENTS

PATINALUSSO is not covered by EU Directive 2004/42/EC.

PATINALUSSO content maximum: 70 g/l VOC

H317 May cause an allergic skin reaction.

Precautionary Statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH 208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1) May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product.

DEKA BOYA SANAYİ ve TİC. A.Ş.