

## DESCRIPTION

SANDECO ART is an acrylic emulsion based, silver and gold pearlescent finished grainy metallic decorative coating.

SANDECO ART VELVET generally has the same features by also having the features of being more thinly grained and softer.

## APPLICATION AREA

SANDECO ART is used on walls, plasters, exposed concrete and wooden surfaces in building interiors, after the surface preparation and with a suitable undercoat.

## PRODUCT FEATURES

- The organic and inorganic pigments it contains provide a vibrant, bright, and grainy texture on the surface.
- It gives a stylish and decorative appearance thanks to the metallic pigments and special fillers it contains.
- Its high water vapor permeability allows water vapor to be expelled, enabling the surface to breathe.
- It is water-based and does not harm human health or the environment.
- Its perfumed feature provides a pleasant smell during application.

## SURFACE PREPARATION

After cleaning all kinds of dirt, oil, blistered paint and dust from the application surfaces, surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and painted surfaces should be primed with SAN DECO DECOPRIMER.

## APPLICATION INSTRUCTIONS

### Environment and Surface Conditions

- During and for 24 hours after the application, it should be ensured that the ambient temperature remains between +5°C minimum and +35°C maximum.
- During the application, it should be ensured that the ambient humidity is below 75%.
- Make sure the humidity value of the application surface is lower than 10%.

## Application:

- After the primer is applied, Sandeco Art / Sandeco Art Velvet should be applied to the surface in a single coat using a wooden brush without dilution.
- While the product is still wet, use circular or straight movements with the brush to create the desired pattern and effect on the surface.
- The application of Sandeco Art Velvet is similar to Sandeco Art. The only difference is that after the pattern is created, the product is burnished with a plastic spatula or trowel to achieve a smooth finish.
- For more detailed application guidance, product application videos can be watched.
- When using multiple batches in the same project, they should be mixed in equal proportions to prevent batch-related variations.
- Touch-ups are not recommended. In case of necessary repairs, the entire affected wall should be reapplied.

## DRYING TIME

The touch dry time at 23°C is 4-5 hours and the complete drying time is 24 hours.

## THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity, and application method, for a single coat application:

- 1 liter covers 6.5 – 8.5 m<sup>2</sup>
- 1 kg covers 5.0 – 6.5 m<sup>2</sup>
- Paint consumption per 1 m<sup>2</sup> area is between 120 – 160 ml and 150 – 200 g

## STORAGE AND SHELF LIFE

The product can be stored in the original sealed package between +5°C - +35°C temperature for 2 years. Make sure that the product is protected from direct sunlight.

## HAZARD STATEMENTS AND EXPLANATIONS

### EU Limit Value (Directive 2004/42/EC)

Category A/I: Decorative effect coatings (water-based): 200 g/l (2010)

Maximum contained in SANDECO ART: 36.5 g/l VOC

Maximum contained in SANDECO ART VELVET: 34 g/l VOC

H317 It can cause allergic skin reactions.

#### **Precautionary Statements and Explanations**

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment (see...on this label).

P272: Contaminated work clothing should not be allowed out of the workplace.



Note: For more information, please check the Safety Data Sheet (SDS) of the product.

This technical data sheet is prepared based on laboratory data under normal conditions. For additional details, consult technical personnel. The manufacturer is not liable for issues arising from incomplete information. The company reserves the right to modify the data. For detailed information on health, safety, and transportation risks, refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified to TS EN ISO 9001, TS EN ISO 14001, and TS 18001 standards.