


SANDECO ART / SANDECO ART VELVET

Metallic Pearl Effect and Quartz Sand Decorative Coating












SANDECO ART/VELVET; developed for interior spaces, is a decorative coating with a granular texture and gold and silver pearlescent finish, achieved through the metallic pigments in its composition.

SANDECO ART VELVET has a finer grain compared to SANDECO ART.



Easy to apply, allowing for the creation of various patterns and textures.

Water-based, safe for human health and environmentally friendly.

 CONTENT: <i>Acrylic-based - water-based</i>	 PACKAGING: <i>1 L ; 2,5 L ; 15 L</i>
 THINNING: <i>Ready to use, do not thin.</i>	 DRYING TIME: <i>Drying Time Touch dry (at 23°C): 4-5 hours</i> <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
 PRIMER: <i>San Deco Decoprimer</i>	 Fully Dry: <i>24 hours</i>
 APPLICATION TOOL: <i>Sandeco Art: Brush, Velvet:Brush + Trowel</i>	 COLORING: <i>Sandeco Art Color Chart</i>
 NUMBER of COATS: <i>1</i>	 VOC: <i>Limit value EU (Directive 2004/42/EC)</i> <i>Category A/I: Decorative effect coatings (water-based): 200 g/l (2010)</i> <i>SANDECO ART: maximum content: 36.5 g/l VOC</i> <i>SANDECO ART VELVET: maximum content: 34 g/l VOC</i>
 STORAGE and SHELF LIFE: <i>In unopened packaging, can be stored in a cool, dry place, protected from direct sunlight, between +5°C and +35°C for 2 years.</i>	

CONSUMPTION - Single Coat : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.*



1 L covers 6,2-7,6 m²,
1 kg covers 4,9-6,0 m² area.
Paint consumption per 1 m²: 130-160 ml and
165-205 g.

APPLICATION AREA

Should be used with its own primer on walls, plaster, raw concrete, and wooden surfaces inside interior spaces after proper surface preparation.

SURFACE PREPARATION

Before application, all dirt, grease, peeling paints, and dust must be removed. Surface irregularities should be corrected with San Deco Acrylic Fine Putty, followed by priming with San Deco Decoprimer.

SURFACE CONDITIONS

During application and until the product is fully dry, the ambient and surface temperature should be at least +5°C and at most +35°C.

Ambient humidity should be below 75% during application.

The moisture content of the surface should be below 10%.

APPLICATION

Sandeco Art/Sandeco Art Velvet should be applied to the surface with a brush in a single coat without thinning, after being mixed homogeneously.

While the product is wet, desired patterns can be created using circular or straight brush movements.

Sandeco Art Velvet is applied using the same method as Sandeco Art; however, after the final pattern, the surface is polished with a plastic spatula or trowel before the product dries.

Alternative techniques may be developed upon request beyond the standard application method.

For more detailed application information, product application videos can be consulted.

If multiple batch numbers are used in the same project, it is recommended to mix the batches evenly before application to avoid batch-based differences.

Local touch-ups are not recommended. If touch-ups are necessary, the entire damaged surface should be reapplied.

HAZARD & PRECAUTIONARY STATEMENTS

- H317: May cause an allergic skin reaction.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P321: Specific treatment required (see label).
P272: Do not take contaminated clothing out of the workplace.

Note: For more information, consult the Safety Data Sheet (SDS) of the product.

This technical sheet is prepared based on laboratory data under normal conditions; for details not sufficiently covered above, consult technical personnel. Otherwise, the manufacturer is not responsible for errors due to insufficient information. The right to modify this information is reserved by our company. Detailed information on product health, safety, and transport risks and precautions can be found in the Material Safety Data Sheet.

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds ISO 9001, ISO 14001, ISO 14064, ISO 45001, ISO 27001 compliance certificates.