



Decorative Paints and Coatings

Sandeco Art / Art Velvet

DESCRIPTION

SANDECO ART is an acrylic emulsion based, silver and gold pearlescent finished grainy metallic decorative coating.

SANDECO ART VELVET generally has the same features by also having the features of being more thinly grained and softer.

APPLICATION AREA

SANDECO ART is used on walls, plasters, exposed concrete and wooden surfaces in building interiors, after the surface preparation and with a suitable undercoat.

PRODUCT FEATURES

- The organic and inorganic pigments it contains provide a vibrant, bright, and grainy texture on the surface.
- It gives a stylish and decorative appearance thanks to the metallic pigments and special fillers it contains.
- Its high water vapor permeability allows water vapor to be expelled, enabling the surface to breathe.
- It is water-based and does not harm human health or the environment.
- Its perfumed feature provides a pleasant smell during application

SURFACE PREPARATION

After cleaning all kinds of dirt, oil, blistered paint and dust from the application surfaces, surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and painted surfaces should be primed with SAN DECO DECOPRIMER.

APPLICATION INSTRUCTIONS

- After the primer is applied, Sandeco Art / Sandeco Art Velvet should be applied to the surface in a single coat using a wooden brush without dilution.
- While the product is still wet, use circular or straight movements with the brush to create the desired pattern and effect on the surface.
- The application of Sandeco Art Velvet is similar to Sandeco Art. The only difference is that after the pattern is created, the product is burnished with a plastic spatula or trowel to achieve a smooth finish.
- During the application and 24 hours after, the ambient temperature should be maintained between +5°C and +35°C.

DRYING TIME

Allow 4-5 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

Sandeco Art / Art Velvet

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

- 1 lt covers 6,5 – 8,5 m² of surface
- 1 kg covers 5,0 – 6,5 m² of surface
- The paint consumption for 1 m² area is 120 – 160 ml and 150 - 200 gr.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; during at a temperature between +5°C and +35°C.

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

**Product Technical Data Sheet No. DP.003.ENG - Rev00 March 2020**

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standards of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.