

# SUPER CEILING

## Water-Based Ultra White Ceiling Paint












SUPER CEILING is an extra white matte ceiling paint.



*Adheres very well to the surface; does not blister or crack.*

*Has high coverage and whiteness.*

*Water-based; environmentally friendly and safe for human health.*

 <b>CONTENT:</b> <i>Acrylic-based - water-based</i>	 <b>PACKAGING:</b> <i>3,5 KG ; 10 KG ; 17,5 KG ; 20 KG</i>
 <b>THINNING:</b> <i>Maximum 20-25% clean water by volume</i>	 <b>DRYING TIME:</b> <i>Drying Time Touch dry (at 23°C): 2-4 hours</i> <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
 <b>PRIMER:</b> <i>San Deco Uniprimer</i>	 <b>Fully Dry:</b> <i>24 hours</i>
 <b>APPLICATION TOOL:</b> <i>Roller, brush, spray</i>	 <b>COLORING:</b> <i>Vision, RAL, NCS</i>
 <b>NUMBER of COATS:</b> <i>2</i>	 <b>VOC:</b> <i>Limit value EU (Directive 2004/42/EC)</i> <i>Category A/A: Interior matt walls and ceilings</i> <i>(water-based): 30 g/l (2010)</i> <i>SUPER CEILING: contains a maximum of 30 g/l VOC.</i>
 <b>STORAGE and SHELF LIFE:</b> <i>Can be stored unopened for 2 years</i> <i>between +5°C and +35°C in a cool,</i> <i>dry place protected from direct</i> <i>sunlight.</i>	

**CONSUMPTION - Single Coat :** *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.*



1 L covers 14.5-15.5 m<sup>2</sup>,  
1 kg covers 8.5-9.5 m<sup>2</sup>.

Paint consumption for 1 m<sup>2</sup>: 65-70 ml and 105-120 g.

### APPLICATION AREA

It is applied together with a suitable primer on properly prepared mineral new ceilings such as rough plaster, concrete, and cement boards, as well as previously painted interior surfaces.

### SURFACE PREPARATION

All kinds of dirt, oil, blistered paint, and dust should be removed from the surfaces to be painted. Surface imperfections should be repaired with San Deco Acrylic Putty Fine. Previously painted and heavily soiled surfaces should be primed with San Deco Uniprimer.

### SURFACE CONDITIONS

During application and until the products are completely dry, the ambient and surface temperature should be at least +5°C and at most +35°C.

The ambient humidity should be below 75% during application.

The surface moisture content should be below 10% before application.

### APPLICATION

Before application, Super Ceiling should be thinned by a maximum of 20-25% clean water by volume and mixed thoroughly until homogeneous.

The product is applied to the surface in two (2) coats using a roller, brush, or spray method. A minimum of 2 hours should be allowed between coats.

### HAZARD & PRECAUTIONARY STATEMENTS AND DESCRIPTIONS

H317: May cause an allergic skin reaction.  
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.  
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364: Take off contaminated clothing and wash it before reuse.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P321: Specific treatment (see label).  
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).



Complies with TS 5808/2012.



Complies with the G regulation.

This technical data sheet is prepared based on laboratory data under normal conditions. For details not sufficiently covered above, please consult technical personnel. Otherwise, the manufacturer cannot be held responsible for errors resulting from insufficient information. The right to make changes to this information is reserved by our company. For detailed information regarding health, safety, and transportation risks and precautions, please refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 compliance certificates.