


# VIVALDI

## Velvet-Textured Metallic Pearl Effect Decorative Coating

VIVALDI is a decorative coating developed for interior use, providing a velvet-like texture with a pearlescent effect.



*Creates a velvet-like texture on the applied surface.*

*Can be cleaned with water.*

*Water-based, environmentally friendly, and harmless to human health.*

<b>CONTENT:</b> <i>Acrylic-based - water-based</i>	<b>PACKAGING:</b> <i>1 L ; 2,5 L</i>
<b>THINNING:</b> <i>Ready to use, do not dilute.</i>	<b>DRYING TIME:</b> <i>Drying Time Touch dry (at 23 °C): 4-5 hours</i> <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
<b>PRIMER:</b> <i>San Deco Decoprimer</i>	<b>Fully Dry:</b> <i>24 hours</i>
<b>APPLICATION TOOL:</b> <i>Trowel or brush</i>	<b>COLORING:</b> <i>Vivaldi Color Chart</i>
<b>NUMBER of COATS:</b> <i>2</i>	<b>VOC:</b> <i>EU limit value (Directive 2004/42/EC)</i> <i>Category A/I: Decorative effect coatings (water-based): 200 g/l (2010)</i> <i>VIVALDI: contains max. 31.2 g/l VOC</i>
<b>STORAGE and SHELF LIFE:</b> <i>Can be stored unopened in a cool and dry place, protected from direct sunlight, between +5 °C and +35 °C, for 2 years.</i>	

**CONSUMPTION - Two Coats :** *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.*

1 L covers 5,8-7,15 m<sup>2</sup>,  
 1 kg covers 5,6-7 m<sup>2</sup> area.  
Paint consumption per 1 m<sup>2</sup>: 140-170 ml and 150-180 g.

### UYGULAMA ALANI APPLICATION AREA

Used on interior walls, plaster, fair-faced concrete, and wooden surfaces after appropriate surface preparation and application of its own primer.

### SURFACE PREPARATION

All dirt, oil, blistered paints, and dust should be removed from the surface.

Surface imperfections should be corrected with San Deco Acrylic Putty Fine, and then primed with San Deco Decoprimer.

### SURFACE CONDITIONS

During application and until the product is completely dry, the ambient and surface temperature should be between +5°C and +35°C.

Ambient humidity should be kept below 75%, and the surface moisture content should be below 10%.

### APPLICATION

Vivaldi should be applied without thinning, after being mixed to a homogeneous consistency.

Apply two (2) coats using a trowel or brush.

The first coat is applied evenly with a trowel or brush.

After the first coat dries, apply the second coat using a trowel or brush to achieve the desired finish.

Wait at least 5 hours between coats.

If more than one batch number is used in the same project, mix batches evenly before application to prevent color or texture differences.

Touch-up is not recommended; for damaged areas, reapply the product to the entire surface.

### HAZARD & PRECAUTIONARY STATEMENTS

- H317: May cause an allergic skin reaction.  
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.  
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364: Take off contaminated clothing and wash it before reuse.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P321: Specific treatment (see label).  
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, refer to the product's Safety Data Sheet (SDS).

This technical data sheet is based on laboratory results obtained under normal conditions. For details not covered above, consult technical personnel. The manufacturer cannot be held responsible for errors arising from insufficient information. The right to make changes to this information is reserved. For detailed information about health, safety, and transportation precautions, refer to the Material Safety Data Sheet.

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified to ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.