


ARISTA

Pearlescent Decorative Paint

ARISTA is a glossy pearlescent decorative paint developed for interior use.



Its pearlescent pigments provide a bright and shimmering effect.

It has a washable surface.

Different patterns and textures can be easily created.

It is water-based, environmentally friendly, and safe for human health.



CONTENT: Acrylic-based – water-based



PACKAGING: 1 L ; 2,5 L ; 7,5 L ; 15 L



THINNING: Ready to use, do not dilute.



DRYING TIME: Drying Time Touch dry (at 23°C): 2-3 hours
*drying time may be longer at higher relative humidity and lower temperature.



PRIMER: San Deco Decoprimer



Fully Dry: 24 hours



APPLICATION TOOL: Roller, effect tampon



COLORING: Arista Color Chart



NUMBER of COATS: 1



STORAGE and SHELF LIFE:
Store unopened in a cool, dry place,
protected from direct sunlight,
between +5°C and +35°C for up to 2
years.



VOC:
Limited value EU (Directive 2004/42/EC)
Category A/I: Decorative effect coatings (water-
based): 200 g/l (2010)
ARISTA: contains a maximum of 44 g/l VOC.

CONSUMPTION - Single Coat : Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.



1 L covers 2,9-3,6 m²,
1 kg covers 2,7-3,3 m² of area.
Paint consumption for 1 m² of surface is 280-340 ml
and 300-370 g.

APPLICATION AREA

It is used on interior walls, plaster, exposed concrete, and wooden surfaces after proper surface preparation with its own primer.

SURFACE PREPARATION

Before application, all kinds of dirt, grease, loose paints, and dust should be removed.

Surface imperfections should be corrected with San Deco Acrylic Putty Fine, and then the surface should be primed with San Deco Decoprimer.

SURFACE CONDITIONS

During application and until the product is fully dry, the ambient and surface temperature should be between +5°C and +35°C.

Ambient humidity should be below 75%.

The moisture level of the surface should be below 10%.

APPLICATION

Arista should be mixed thoroughly until homogeneous and applied undiluted to the surface with a roller.

After one coat is applied with a roller, before it begins to dry, a suitable decorative tampon should be used to create the desired texture.

For large surface areas, it is recommended to work with two people: one applying the paint with a roller, the other giving the effect before the paint begins to dry.

For more detailed information, product application videos can be viewed.

If more than one batch number is used in the same project, to avoid batch-to-batch differences, the batches should be mixed in equal proportions before application.

Local touch-ups are not recommended. For repairs, the entire affected area should be recoated.

HAZARD & PRECAUTIONARY STATEMENTS

- H317: May cause an allergic skin reaction.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P321: Specific treatment (see label).
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, refer to the product's Safety Data Sheet (SDS).

This technical data sheet is prepared based on laboratory data under normal conditions. For additional details, consult technical personnel. The manufacturer accepts no liability for errors resulting from insufficient information. The right to modify this information is reserved by the company. For detailed information regarding product health, safety, transportation risks, and precautions, please refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified with ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.