

# PATINALUSSO

## Pearl-Effect Decorative Topcoat Paint

PATINALUSSO is a decorative topcoat paint developed for application on the surfaces of acrylic and lime-based coating products, giving the applied surface a pearlescent effect appearance.



*Easy to apply.*

*Enhances the gloss of the applied surfaces, creating silver or gold pearlescent finishes.*

*Its special wax content provides a soft touch to the surface.*

*It is water-based, friendly to human health and the environment.*

 <b>CONTENT:</b> Water-based	 <b>PACKAGING:</b> 1 L
 <b>THINNING:</b> Ready to use, does not require thinning.	 <b>DRYING TIME:</b> Drying Time Touch dry (at 23°C): 1-2 hours <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
 <b>PRIMER:</b> -	 <b>Fully Dry:</b> 24 hours
 <b>APPLICATION TOOL:</b> Steel trowel	 <b>COLORING:</b> -
 <b>NUMBER of COATS:</b> 1	 <b>VOC:</b> Not covered by the EU limit value (Directive 2004/42/EC). PATINALUSSO: contains a maximum of 70 g/l VOC.
 <b>STORAGE and SHELF LIFE:</b> Can be stored for 2 years between +5°C and +35°C, in its unopened packaging, in a cool and dry place protected from direct sunlight.	

**CONSUMPTION - Single Coat :** Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.



1 L covers 16-20 m<sup>2</sup>,  
1 kg covers 15-19 m<sup>2</sup>.

Paint consumption per 1 m<sup>2</sup> surface: 50-60 ml or 52-62 g.

### APPLICATION AREA

It is applied on the surfaces of acrylic and lime-based decorative coatings in interior spaces.

### SURFACE PREPARATION

All dirt, oil, and dust should be removed from the surface before application.

### SURFACE CONDITIONS

During application and until the products are completely dry, the ambient and surface temperature should be at least +5°C and at most +35°C.

During application, ambient humidity should be below 75%.

The surface moisture content should be below 10%.

### APPLICATION

Patinalusso should be applied without thinning, after being mixed homogeneously, in a single thin layer using a trowel.

After the product dries, the surface should be polished with a clean and dry cloth or a polishing machine.

Apart from the standard application method, different techniques can be developed optionally using a brush.

For more detailed information about the application, product application videos may be watched.

If more than one batch number is used in the same project, to prevent batch-based differences, it is recommended to mix the batches in equal proportions before application.

Local retouching is not recommended. In cases requiring repair, it is advised to reapply the product to the entire affected surface.

### HAZARD & PRECAUTIONARY STATEMENTS AND DESCRIPTIONS

- H317: May cause an allergic skin reaction.  
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.  
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364: Take off contaminated clothing and wash it before reuse.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P321: Specific treatment (see label).  
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product's Safety Data Sheet (SDS).

This technical data sheet is prepared based on laboratory data under normal conditions; for any details not sufficiently covered above, please consult technical personnel. Otherwise, the manufacturer cannot be held responsible for errors arising from insufficient information. Our company reserves the right to change this information. If necessary, detailed information regarding the health, safety, and transportation risks and precautions of the products can be found in the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds conformity certificates for ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.