

MOIRE












Suede-Look Decorative Paint

MOIRE is a matte decorative paint developed for interiors, offering a suede-like appearance.



It is easy to apply and allows for the creation of various patterns and textures.

It is water-based, environmentally friendly, and safe for human health.

 CONTENT: <i>Acrylic-based - water-based</i>	 PACKAGING: <i>2,5 L ; 15 L</i>
 THINNING: <i>Ready to use, do not dilute.</i>	 DRYING TIME: <i>Drying Time Touch dry (at 23 °C): 1-2 hours</i> <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
 PRIMER: <i>San Deco Decoprimer</i>	 Fully Dry: <i>24 hours</i>
 APPLICATION TOOL: <i>Brush</i>	 COLORING: <i>Moire Color Chart</i>
 NUMBER of COATS: <i>2</i>	 VOC: <i>Limit value under EU Directive 2004/42/EC Category A/I: Decorative effect coatings (water-based): 200 g/l (2010) MOIRE: contains a maximum of 20 g/L VOC</i>
 STORAGE and SHELF LIFE: <i>Can be stored unopened for 2 years in a cool and dry place, protected from direct sunlight, between +5 °C and +35 °C.</i>	

CONSUMPTION - Single Coat : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.*



1 L covers 6,8-8,4 m²,
1 kg covers 5,8-7,1 m² of area.
Paint consumption for 1 m² of surface is 120-145 ml and 140-170 g.

APPLICATION AREA

It is used on the interior walls, plaster, fair-faced concrete, and wooden surfaces of spaces after appropriate surface preparation, together with its own primer.

SURFACE PREPARATION

All dirt, oil, blistered paints, and dust should be cleaned from the surface before application. Surface defects should be corrected with San Deco Acrylic Putty Fine, then primed with San Deco Decoprimer.

SURFACE CONDITIONS

During application and until the product is completely dry, the ambient and surface temperature should be at least +5°C and at most +35°C.

Ambient humidity should be below 75%.

The surface moisture level should be below 10%.

APPLICATION

Moire should be applied to the surface with a brush in two (2) coats after thorough mixing without dilution.

The first coat should be applied freely and randomly using the bursh.

The same process is repeated for the second coat to achieve the desired appearance. Wait at least 3-4 hours between coats.

Apart from the standard application method, different techniques can also be developed if desired.

For more detailed application information, product application videos can be watched.

If more than one batch number is used in the same project, it is recommended to mix them in equal proportions before application to avoid batch-based differences.

Local retouching is not recommended. In cases requiring retouching, it is advised to reapply the product to the entire damaged surface.

HAZARD & PRECAUTIONARY STATEMENTS AND EXPLANATIONS

H317: May cause an allergic skin reaction.

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment (see label).

P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, refer to the product's Safety Data Sheet (SDS).

This technical data sheet is prepared based on laboratory data under normal conditions. For details not covered above, please consult technical personnel. Otherwise, any errors arising from insufficient information will not be the manufacturer's responsibility. The right to change this information is reserved by our company. For detailed information regarding the product's health, safety, and transport risks and precautions, please refer to the Material Safety Data Sheet.

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 certification.