

# ROCKCREST OPTIMUM

## Pure Acrylic Granular Exterior Paint

ROCKCREST OPTIMUM is a medium-textured, granular, silk-matt, flexible, water-based pure acrylic exterior paint.



*Provides high water impermeability.*

*Excellent resistance to alkalis.*

*Highly durable under exterior conditions.*

*Offers excellent resistance to weather and water, extending paint film life by preventing mold and fungus formation.*

*High water vapor permeability allows moisture to escape easily, accelerating drying.*

*Thanks to its crack-bridging property, it resists capillary cracks caused by building settlement over time.*

*Water-based, environmentally friendly, and safe for human health.*



CONTENT: 100% Pure Acrylic - Water-based



PACKAGING: 13.5 L; 15 L



THINNING: Ready to use; do not dilute.



DRYING TIME: Drying Time Touch dry (at 23°C): 5-6 hours  
*\*drying time may be longer at higher relative humidity and lower temperature.*



PRIMER: San Deco Decoprimer



Fully Dry: 24-48 hours



APPLICATION TOOL: Coral roller



COLORING: Vision System



NUMBER of COATS: 2



STORAGE and SHELF LIFE:  
Can be stored unopened for 2 years  
between +5°C and +35°C in a cool,  
dry place away from direct sunlight.



VOC:  
EU Limit Value (Directive 2004/42/EC)  
Category A/c: Exterior walls of mineral substrates  
(water-based): 40 g/L (2010)  
ROCKCREST OPTIMUM contains a maximum of 32 g/  
L VOC.

CONSUMPTION - Single Coat : Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.



1 L covers 1.35-5.45 m<sup>2</sup>

1 kg covers 1-2.5 m<sup>2</sup>

Paint consumption per 1 m<sup>2</sup>: 290-740 ml and  
400-1000 g.

### APPLICATION AREA

Suitable for use on the exterior surfaces of all types of buildings, on plaster, satin plaster, gypsum, fair-faced concrete, and gypsum board surfaces.

### SURFACE PREPARATION

All dirt, oil, blistered paint, and dust must be removed from the surface before application. Surface defects should be repaired using San Deco Acrylic Putty Thick, then primed with San Deco Decoprimer.

### SURFACE CONDITIONS

During application and until complete drying, ambient and surface temperatures should be between +5°C and +35°C.

Do not apply under direct sunlight.

Surfaces must be completely dry before painting.

Ambient humidity should be below 75%.

Surface moisture content should be below 10%.

### APPLICATION

ROCKCREST OPTIMUM should be mixed thoroughly before application without dilution.

Apply evenly in two (2) coats using a coral roller from bottom to top.

Wait at least 5-6 hours between coats for proper drying.

If multiple production batches are used within the same project, mix them in equal proportions before application to avoid tonal or textural differences.

### HAZARD & PRECAUTIONARY STATEMENTS

- H317: May cause an allergic skin reaction.  
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.  
P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.  
P362 + P364: Take off contaminated clothing and wash it before reuse.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P321: Specific treatment (see label).  
P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more detailed information, refer to the product's Safety Data Sheet (SDS).

This technical data sheet is based on laboratory data obtained under standard conditions. For details not sufficiently covered above, please consult technical personnel. The manufacturer cannot be held responsible for any errors resulting from insufficient information. Our company reserves the right to amend this information. For detailed information regarding health, safety, transport risks, and precautions, refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified under ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.