

PRODUCT DESCRIPTION

A water-based roof paint formulated with acrylic emulsion and siloxane additives, specially designed for roof insulation and aesthetics.

APPLICATION AREA

It can be safely used for protection and insulation on all types of roof coatings.

PRODUCT FEATURES

- Highly water-repellent feature.
- Resistant to weather conditions such as rain, snow, extreme heat, and extreme cold, as well as abrasion.
- Offers excellent coverage.
- Allows water vapor to escape with its high water vapor permeability, enabling the surface to breathe.
- Water-based, odorless, and does not harm human health or the environment.

SURFACE PREPARATION

- All surfaces to be painted must be cleaned of oil, dirt, and any loose layers that may prevent adhesion. The surface must be clean and dry.
- The painted surfaces must be sloped to prevent water accumulation.

APPLICATION INSTRUCTIONS

- Before application, ROOF PAINT must be mixed thoroughly until homogeneous and applied in a single coat using a specialized spray gun without dilution.
- During application and for the following 24 hours, ensure that the ambient temperature is between a minimum of +5°C and a maximum of +35°C.

DRYING TIME

At 23°C:

- Touch dry: 4-6 hours
- Fully dry: 24 hours

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88

PACKAGING

15 L

THEORETICAL CONSUMPTION

Depending on surface smoothness, absorption, and application techniques:

- 1 liter covers 7.0–10.0 m²
- 1 kg covers 6.5–9.0 m²
- Paint consumption per 1 m²: 100–140 ml and 110–150 g

STORAGE

Can be stored for 1 year in its unopened package, in a cool and dry place, protected from direct sunlight, at temperatures between +5°C and +35°C.

HAZARD STATEMENTS

H317: May cause allergic skin reactions.

H412: Harmful to aquatic life with long-lasting effects.

PRECAUTIONARY STATEMENTS

P261: Avoid breathing dust/fumes/gas/mist/vapors/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P273: Avoid release into the environment.

P101: If medical advice is needed, have the product container or label at hand.

P102: Keep out of reach of children.

Note: For more technical information, please refer to the **Material Safety Data Sheet (MSDS)** of the product.