

## PRODUCT DESCRIPTION

A water-based roof paint formulated with acrylic emulsion and siloxane additives, specially designed for roof insulation and aesthetics.

## APPLICATION AREA

It can be safely used for protection and insulation on all types of roof coatings.

## PRODUCT FEATURES

- Highly water-repellent feature.
- Resistant to weather conditions such as rain, snow, extreme heat, and extreme cold, as well as abrasion.
- Offers excellent coverage.
- Allows water vapor to escape with its high water vapor permeability, enabling the surface to breathe.
- Water-based, odorless, and does not harm human health or the environment.

## SURFACE PREPARATION

- All surfaces to be painted must be cleaned of oil, dirt, and any loose layers that may prevent adhesion. The surface must be clean and dry.
- The painted surfaces must be sloped to prevent water accumulation.

## APPLICATION INSTRUCTIONS

- Before application, HYDRO ROOF PAINT must be mixed thoroughly until homogeneous and applied in a single coat using a specialized spray gun without dilution.
- During application and for the following 24 hours, ensure that the ambient temperature is between a minimum of +5°C and a maximum of +35°C.

## DRYING TIME

At 23°C:

- Touch dry: 4-6 hours
- Fully dry: 24 hours

**DEKA BOYA SANAYİ ve TİC. A.Ş.**

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56  
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88

## PACKAGING

15 L

## THEORETICAL CONSUMPTION

Depending on surface smoothness, absorption, and application techniques:

- 1 liter covers 7.0–10.0 m<sup>2</sup>
- 1 kg covers 6.5–9.0 m<sup>2</sup>
- Paint consumption per 1 m<sup>2</sup>: 100–140 ml and 110–150 g

## STORAGE

Can be stored for 1 year in its unopened package, in a cool and dry place, protected from direct sunlight, at temperatures between +5°C and +35°C.

## HAZARD STATEMENTS

H317: May cause allergic skin reactions.

H412: Harmful to aquatic life with long-lasting effects.

## PRECAUTIONARY STATEMENTS

P261: Avoid breathing dust/fumes/gas/mist/vapors/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P273: Avoid release into the environment.

P101: If medical advice is needed, have the product container or label at hand.

P102: Keep out of reach of children.

**Note:** For more technical information, please refer to the **Material Safety Data Sheet (MSDS)** of the product.