

## 1. PRODUCT DESCRIPTION

ROCKCREST HYPER is a 100% pure acrylic-based, medium-textured, semi-gloss, flexible, water-based exterior paint.

## 2. APPLICATION AREA

It is suitable for use on the exterior surfaces of all types of buildings, including plaster, satin plaster, gypsum, exposed concrete, and plasterboard. Thanks to its special formulation, it provides superior protective properties in addition to decorative designs for exterior facades.

## 3. PRODUCT FEATURES

- ROCKCREST HYPER is a 100% pure acrylic-based product with high water impermeability.
- ROCKCREST HYPER has crack bridging properties against microcracks that may occur as the building settles over time.
- ROCKCREST HYPER has carbon dioxide and chloride ion diffusion properties.
- ROCKCREST HYPER has high water vapor permeability, which allows the surface to easily expel moisture and accelerates the drying of the product.
- ROCKCREST HYPER offers excellent resistance to air and water, extending the time of the paint film by preventing mold and fungus formation.
- ROCKCREST HYPER is water-based, odorless, and doesn't harm human health or the environment.

## 4. SURFACE PREPARATION

Before application, remove all dirt, grease, peeling paint, and dust from the surface. Surface imperfections should be corrected with SAN DECO ACRYLIC PUTTY THICK exterior filler and primed with SAN DECO DECOPRIMER.

## 5. APPLICATION INSTRUCTIONS

### 5.1. Environmental and Surface Conditions

- During and for 24 hours after the application, the ambient temperature should be between +5°C and +35°C.
- During application, the ambient humidity should be below 75%.
- The moisture level of the surface to be painted should be below 10%.

## 5.2. Application

- ROCKCREST HYPER should be applied undiluted in two coats using a coral roller.
- Allow 5-6 hours for the product to dry between coats.
- For both coats, apply the product homogeneously from bottom to top using the coral roller.
- For more detailed information about the application, please watch the product application videos.
- If multiple batches are used in the same project, it is recommended to mix the batches evenly to avoid any differences between them.

## 6. DRYING TIME

At 23°C, touch dry in 5-6 hours, full drying time is 24-48 hours.

## 7. THEORETICAL CONSUMPTION

Depending on surface smoothness, absorbency, and application techniques, for a single coat application:

- 1 liter covers 2 – 4 m<sup>2</sup>,
- 1 kg covers 1.6 – 3.3 m<sup>2</sup>.
- Coverage per m<sup>2</sup> is 230 - 470 ml and 300 - 600 gr.

## 8. STORAGE AND SHELF LIFE

The unopened packaging can be stored for 2 years in a cool, dry place, protected from direct sunlight, between +5°C and +35°C.

## 9. HAZARD STATEMENTS AND EXPLANATIONS

EU Limit Values (Directive 2004/42/EC)

Category A/c: Exterior walls of mineral substrates (water-based): 40 g/l (2010)

ROCKCREST HYPER contains a maximum of 38.5 g/l VOC.

H317: May cause an allergic skin reaction.

## 10. PRECAUTIONARY STATEMENTS AND EXPLANATIONS

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment (see label).

P272: Do not take contaminated clothing out of the workplace.

**Note:** For more information, please refer to the Safety Data Sheet (SDS) of the product.

This technical datasheet has been prepared based on laboratory data, and if more details are needed, consult with technical personnel. The manufacturer does not accept responsibility for errors arising due to insufficient information. The right to modify this information is reserved by our company. For detailed information regarding health, safety, transportation risks, and precautions, refer to the Material Safety Data Sheet (MSDS). This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which is certified according to TS EN ISO 9001, TS EN ISO 14001, and TS 18001 standards.