



Peerless paint, peerless places.

Exterior Surface Products

Teramix Hydro Ultra

DESCRIPTION

TERAMIX HYDRO ULTRA is an acrylic emulsion based, water-repellant due to the polysiloxane additive it contains, elastomeric, grain-textured, decorative coating.

APPLICATION AREA

It is used as a coating material with the appropriate primer on facades of all kinds of buildings, on black cement plasters, exposed cements, cement sheets and thermal insulation systems.

SURFACE PREPARATION

After all kinds of dirt, oil, blistered paint and dust are cleaned from the surfaces of application, the surface defects should be smoothened with SAN DECO ACRYLIC PUTTY EXTERIOR. Already-painted surfaces should be primed with SAN DECO UNIPRIMER as well as the surfaces to be newly painted. It is recommended to use the primer with the same color as the one of the selected facades.

FEATURES

- For being elastomeric, it is a material that can maintain its elasticity even at low temperatures; it serves as a bridge in cracks formed on the surface.
- It is water-repellent thanks to the silicone additive and resin it contains.
- Due to the fact that it is more elastic compared to cement-based products, it serves as a bridge in the cracks on the surface it will be applied on.
- It is not affected by cracks that may occur as a result of buildings subsiding.
- It covers the defects on the surface due to the thick film layer it forms during application.
- It is not affected by external factors, weather conditions such as rain, snow, humidity, extreme heat or extreme cold, and its colors do not fade.
- It is resistant to UV and alkali.
- It is water-based, does not smell or not harm human health and environment

APPLICATION INSTRUCTIONS

- TERAMIX HYDRO ULTRA should be thoroughly mixed until a homogeneous consistency is achieved without being diluted.
- TERAMIX HYDRO ULTRA is applied as a single layer with the help of a trowel. The application thickness should be adjusted according to the largest pattern stones contained in the product. The surface should be patterned with a plastic trowel in circular motions.
- Before the application of TERAMIX HYDRO ULTRA, surface should be dried completely.
- It should be paid attention that the ambient temperature should be minimum +5°C and maximum +35°C within 24 hours during and after the application.

DRYING TIME

Allow 4-6 hours for touch dry and 24-48 hours for complete dry at 23°C and %50 RH environment conditions.

THEORETICAL CONSUMPTION

For one-layer application, depending on the surface smoothness, absorbency and application techniques;

- 1,00 – 1,30 m² with 1 lt
- 0,65 – 0,75 m² area is painted with 1 kg.
- Paint consumption for an area of 1 m² is 950 – 1000 ml and 1400 – 1500 gr

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88



Peerless paint, peerless places.

Exterior Surface Products

Teramix Hydro Ultra

STORAGE

It can be stored in its unopened package, cool and dry environments, protected from direct sunlight at between +5°C and +35°C.

Hazard Statements

H317 May cause an allergic skin reaction.

Precautionary Statements

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment (see label).

P272: Do not take contaminated clothing out of the workplace.

EUH208 Contains: chloromethylisothiazolinone and methylisothiazolinone (3:1); 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1); 2-methylisothiazol-3(2H)-one and 1,2-benzisothiazol-3(2H)-one.includes. May produce an allergic reaction.

EUH210 Safety data sheet available on request

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or m

Note: For more information, please check the Safety Data Sheet (SDS) of the product

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88