

1. PRODUCT DESCRIPTION

Travertino Interior and Travertino Exterior are mineral-based, natural decorative coatings that create a travertine stone appearance on applied surfaces.

2. APPLICATION AREA

Travertino Interior is used on interior walls, plaster, exposed concrete, and wooden surfaces after proper surface preparation and primer application.

Travertino Exterior is used on exterior walls, plaster, and exposed concrete surfaces after proper surface preparation and primer application.

3. PRODUCT FEATURES

- Allows different textures and effects to be created depending on the applicator's skill.
- Its exceptional water vapor permeability promotes the elimination of moisture, allowing the surface to breathe.
- Water-based, making it environmentally friendly and safe for human health.
- Contains a pleasant fragrance, enhancing the ambiance of the applied area.

4. SURFACE PREPARATION

Before applying Travertino Interior, dirt, oil, and dust on the surface should be removed, surface imperfections should be corrected with San Deco Acrylic Putty Interior, and primed with San Deco Decoprimer.

Before applying Travertino Exterior, dirt, oil, and dust on the surface should be removed, surface imperfections should be corrected with San Deco Acrylic Putty Exterior, and primed with Decoprimer.

5. APPLICATION INSTRUCTIONS

5.1 Environmental and Surface Conditions

- During and for 24 hours after the application, it should be ensured that the ambient temperature remains between +5°C minimum and +35°C maximum.
- During the application, it should be ensured that the ambient humidity is below 75%.
- Make sure the humidity value of the application surface is lower than 10%.

5.2 Application

- Travertino Interior / Travertino Exterior should be applied with a stainless steel trowel in the first coat, without dilution, at a minimum thickness of 1 mm. The second coat should be applied at least 6 hours after the first coat.
- Before the second coat dries completely, a special sponge or brush/trowel should be used to create the desired effect.
- After, the surface should be burnished with a stainless steel trowel to achieve a smooth finish.
- For detailed application instructions, product application videos can be watched.
- When using multiple batches within the same project, to avoid batch variations, it is recommended to mix batches evenly before application.

6. DRYING TIME

Travertino Interior: The touch dry time at 23°C is 2-3 hours and the complete drying time is 48 hours.

Travertino Exterior: The touch dry time at 23°C is 5-6 hours and the complete drying time is 48 hours.

7. THEORETICAL CONSUMPTION

TRAVERTINO INTERIOR

Depending on surface smoothness, porosity and application methods, for a single coat application:

1 liter covers 1,75 – 2,35 m².

1 kg covers 1,00 - 1,35 m².

The paint consumption for 1 m² is between 425-570 ml and 750-1000 gr.

TRAVERTINO EXTERIOR

Depending on surface smoothness, porosity and application methods, for a single coat application:

1 liter covers 1,5 – 2,0 m².

1 kg covers 1,00 - 1,35 m².

The paint consumption for 1 m² is between 470-680 ml and 750-1100 gr.

8. STORAGE AND SHELF LIFE

The product can be stored in the original sealed package between +5°C/+35°C temperature for 2 years. Make sure that the product is protected from direct sunlight.

9. HAZARD STATEMENTS AND EXPLANATIONS

EU Limit Value (Directive 2004/42/EC)

Category A/l: Decorative effect coatings (water-based): 200 g/l (2010)

TRAVERTINO INTERIOR VOC content: Maximum 46.2 g/l

TRAVERTINO EXTERIOR VOC content: Maximum 39 g/l

H317: May cause an allergic skin reaction.

10. PRECAUTIONARY STATEMENTS

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment (see...on this label).

P272: Contaminated work clothing should not be allowed out of the workplace

Note:

For more details, refer to the **Safety Data Sheet (SDS)**.

This technical data sheet is prepared based on laboratory data under normal conditions. For further details, consult technical personnel. The manufacturer is not responsible for errors resulting from incomplete information. The company reserves the right to modify the data. For comprehensive information on health, safety, and transportation risks, refer to the **Material Safety Data Sheet (MSDS)**.

This product is manufactured by **Deka Boya Sanayi ve Tic. A.Ş.**, certified to **TS EN ISO 9001**, **TS EN ISO 14001**, and **TS 18001** standards.