

TRAVERTINO EXTERIOR

Travertine and Natural Stone Effect Decorative Coating

TRAVERTINO EXTERIOR is a mineral-based decorative coating that provides a travertine appearance on the applied surface.



It allows obtaining various textures through different application techniques.

Thanks to its high water vapor permeability, it enables vapor to escape and allows the surface to breathe.

It is water-based, environmentally friendly, and harmless to human health.

 CONTENT: Acrylic-based - water-based	 PACKAGING: 10 KG ; 20 KG
 THINNING: Ready to use, do not dilute.	 DRYING TIME: Drying Time Touch dry (at 23 °C): 5-6 hours <small>*drying time may be longer at higher relative humidity and lower temperature.</small>
 PRIMER: San Deco Decoprimer	 Fully Dry: 48 hours
 APPLICATION TOOL: Steel Trowel / Texture Tool	 COLORING: -
 NUMBER of COATS: 2	
 STORAGE and SHELF LIFE: Can be stored for 2 years in its unopened packaging, in a cool and dry place, protected from direct sunlight, between +5 °C and +35 °C.	 VOC: Limiting value EU (Directive 2004/42/EC) Category A/I: Decorative effect coatings (water-based): 200 g/l (2010) TRAVERTINO EXTERIOR: contains max: 39 g/l VOC

CONSUMPTION - Single Coat : Consumption may vary depending on the type, absorbency, and structure of the surface, as well as the application techniques. For precise consumption, a controlled sample application should be performed.



1 L covers 1.5-2.0 m²,
1 kg covers 1-1.35 m² area.
Paint consumption per m²: 470-680 ml and 750-1100 g.

APPLICATION AREA

It should be used on the outer walls, plaster, exposed concrete, and wooden surfaces of spaces after proper surface preparation and together with its own primer.

SURFACE PREPARATION

After removing all kinds of dirt, oil, loose paints, and dust from the surfaces to be applied, surface imperfections should be corrected with San Deco Acrylic Putty Coarse and then primed with San Deco Decoprimer.

SURFACE CONDITIONS

During the application and until the product is completely dry, care should be taken that the ambient and surface temperature is at least +5°C and at most +35°C.

Application should not be carried out under direct sunlight.

Surfaces to be painted must be completely dry.

During the application, the ambient humidity should be below 75%.

The moisture content of the surface to be applied should be below 10%.

APPLICATION

Travertino Exterior should be applied without thinning, using a steel trowel, with a first coat of at least 1 mm thickness.

After at least 6 hours from the first coat, the second coat can be applied.

Before the second coat is completely dry, texture is given to the surface with a texture trowel.

To obtain a smooth final coat, the surface is burnished with a steel trowel.

For more detailed information on application, product application videos can be watched.

If more than one batch number is used in the same project, it is recommended to mix the batches in equal proportion before application to prevent batch-based differences.

Local retouching is not recommended. In cases where retouching is required, it is recommended to reapply the product to the entire damaged surface.

HAZARD & PRECAUTIONARY STATEMENTS AND EXPLANATIONS

H317: May cause an allergic skin reaction.

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment (see label).

P272: Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please refer to the product Safety Data Sheet (SDS).

Since this technical data sheet is prepared based on laboratory data under normal conditions, please consult technical personnel for details not sufficiently covered above. Otherwise, the manufacturer is not responsible for any errors arising from lack of information. The right to make changes to this information is reserved by our company. For detailed information regarding the health, safety, and transportation risks and precautions of the products, you can refer to the Material Safety Data Sheet.

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds certificates of conformity to ISO 9001, ISO 14001, ISO 14064, ISO 45001, ISO 27001 standards.